WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER LOCATION OF WATER WELL: TOWNSHIP NUMBER RANGE NUMBER NWSWHarvey SW29 1/4 1/4 1/4 T 23 s **R 2W** E/W Distance and direction from nearest town or city street address of well if located within city? 1.3 miles No. of Halstead Road on Golden Prairie Road, 3 m. West of Halstead (4 logs on 1 permit) WICHITA, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource 455 N. Main RR#,ST. ADDRESS,BOX #: 20110037 CITY, STATE Wichita, Kansas Application Number: ZIP CODE: 40 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. 10 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NW NE Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ≌ 12 Bore Hole Diameter ft. WELL WATER TO BE USED AS 11. Injection well 9. Dewatering SW SF 7. Lawn and garden only 3. Feedlot 5. Public water supply 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO Was Water Well Disinfected? (YES) submitted NO TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 20 ft., Dia. in. Dia. ft. to in. to 12 Casing height above land surface: in. Weight: 5.52 lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 40 ft.. From to From ft. From From ft... ft to ft. 20 GRAVEL PACK INTERVALS: ft. 40 From From ft.. ft. to ft. From ft. to ft.. From ft. **GROUT MATERIALS:** Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite 0 Grout Intervals: ft. 20 ft., ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines None apparent 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit Direction from well? How many feet? LITHOLOGIC LOG From Τо LITHOLOGIC LOG From Тο topsoil 3 fine sand 15 40 clav Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed 3. under my jurisdiction and 1/31/2011 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/4/2011 Todd S. Harp by (signature) under the business name of Harp Well and Pump Service