

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Harvey	SE NW 1/4 SE 1/4	35	T 23 S	R 2W

Distance and direction from nearest town or city street address of well if located within city?

201 Main, Halstead, Kansas

2 WATER WELL OWNER:	RR#, St. Address, Box #	Red's Standard Service Attn: B. Wenger	Board of Agriculture, Division of Water Resources
City, State, ZIP Code	P.O. Box 295, Newton, KS 67114	Application Number:	-----

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
	30	-----
	Depth(s) Groundwater Encountered 1. 24.7	ft. 2. ----- ft. 3. -----
	WELL'S STATIC WATER LEVEL 22.65	ft. below land surface measured on mo/day/yr 3/22/95
	Pump test data: Well water was ----- ft. after ----- hours pumping ----- gpm	
	Est. Yield ----- gpm: Well water was ----- ft. after ----- hours pumping ----- gpm	
	Bore Hole Diameter 8.625 to 30	ft., and ----- in. to ----- ft.
	WELL WATER TO BE USED AS:	
	5 Public water supply 8 Air conditioning 11 Injection well	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-3	
	Was a chemical/bacteriological sample submitted to Department? Yes ----- No X	If yes, mo/day/yr sample was submitted -----
	Water Well Disinfected? Yes ----- No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ----- Clamped -----
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded -----
Blank casing diameter 2	in. to 20	ft., Dia	Threaded X
Casing height above land surface 0	in., weight	SCH. 40 PVC	lbs./ft. Wall thickness or gauge No. -----
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	5 Gauzed wrapped
2 Louvered shutter	4 Key punched	7 Torch cut	8 Saw cut
SCREEN-PERFORATED INTERVALS:	From 20	ft. to 30	ft., From -----
SAND GRAVEL PACK INTERVALS:	From 18	ft. to 30	ft., From -----
	From -----	ft. to -----	ft., From -----

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0	ft. to 16	ft., From 3	ft. to 18
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well?			13 Insecticide storage	16 Other (specify below)
			How many feet?	Contaminated site

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	0.50	Asphalt			Flush Mount Wai
0.50	24.50	Silty Clay			Richard Harper
24.50	30.00	Silty Sand			2/20/95
30.00	TD	End of Borehole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/14/95	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No.	585	This Water Well Record was completed on (mo/day/yr) 3/28/95
under the business name of	Associated Environmental, Inc.	by (signature) Johnson for Davis Duncan