

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Harvey	SE NW 1/4 SE 1/4	35	T 23 S	R 2 W

Distance and direction from nearest town or city street address of well if located within city?

201 Main, Halstead, Kansas

2 WATER WELL OWNER:	RR#, St. Address, Box #	City of Halstead	Attn: Danny Bisoni	Board of Agriculture, Division of Water Resources
City, State, ZIP Code	303 Main, Halstead, Ks	67056	Application Number:	-----

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
	30	ft. ELEVATION: 23.6
	Depth(s) Groundwater Encountered 1. 23.6	ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 20.78	ft. below land surface measured on mo/day/yr 3/22/95
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield gpm: Well water was	ft. after hours pumping gpm
	Bore Hole Diameter 8.625	to 30 ft. and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No X	If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Glamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 20	ft. Dia	in. to ft. Dia	Threaded X
Casing height above land surface 0	in. weight SCH. 40 PVC	lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 20 ft. to 30	ft. From ft. to ft.	
SAND GRAVEL PACK INTERVALS:	From 18 ft. to 30	ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0	ft. to 16	ft. From 16	ft. to 18	ft. From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well?	How many feet?	13 Insecticide storage	16 Other (specify below)	
		Contaminated site		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	2.00	Soil, Silty Clay			Flush Mount Wai
2.00	19.00	Silty Clay			Richard Harper
19.00	24.00	Sandy Clay			2/20/95
24.00	30.00	Silty Sand			
30.00	TD	End of Borehole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/14/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 3/28/95 under the business name of Associated Environmental, Inc. by (signature) [Signature]
--