


1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NW 1/4 Section Number 6 Township Number T 23 S Range Number R 23 E
 County: Hodgeman

Distance and direction from nearest town or city street address of well if located within city?
610 S. Main Jetmore KS

2 WATER WELL OWNER: Lloyd Nusser Chevrolet P.O. Box 175
 RR#, St. Address, Box #: 610 S. Main Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Jetmore, KS 67854 Application Number: 2

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 62.0 ft. ELEVATION: 62.0 ft.
 Depth(s) Groundwater Encountered 1. 50.0 ft. 2. 50.0 ft. 3. 50.0 ft.
 WELL'S STATIC WATER LEVEL: 50.0 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm
 Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter: NA in. to NA ft., and NA in. to NA ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No No Yes; If yes, mo/day/yr sample was submitted No
 Water Well Disinfected? Yes No No Yes

5 TYPE OF CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Welded Clamped Threaded
 Blank casing diameter: 2.0 in. to 2.0 ft., Dia. 2.0 in. to 2.0 ft., Dia. 2.0 in. to 2.0 ft.
 Casing height above land surface: 0 in., weight 0 lbs./ft. Wall thickness or gauge No. 0
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 0.0 ft. to 0.5 ft., From 0.5 ft. to 2.0 ft., From 2.0 ft. to 62.0 ft.
 GRAVEL PACK INTERVALS: From 0.0 ft. to 0.5 ft., From 0.5 ft. to 2.0 ft., From 2.0 ft. to 62.0 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0.0 ft. to 0.5 ft., From 0.5 ft. to 2.0 ft., From 2.0 ft. to 62.0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			<u>0.0</u>	<u>0.5</u>	<u>Cement</u>
			<u>0.5</u>	<u>2.0</u>	<u>Cement</u>
			<u>2.0</u>	<u>62.0</u>	<u>Bentonite</u>

Well No. ~~0067853~~ 0067853 MN-3
Deff. Field Services #TB-038-98

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/15/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 4/1/99 under the business name of TEOT (Deffonbaugh Field Services) by (signature) Ron Wood by P.O.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4