

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SW 1/4 SW 1/4		Section Number 24	Township Number T 23 S		Range Number R 3 W	
Distance and direction from nearest town or city street address of well if located within city? 3 miles East of Burrton, KS.								
2 WATER WELL OWNER: Gordon Schmidt RR#, St. Address, Box # : 10320 N. Wheat State Rd. City, State, ZIP Code : Inman, KS 67546 Board of Agriculture, Division of Water Resources Application Number: 41,990								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION:					
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL .39 ft. below land surface measured on mo/day/yr 4/9/96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1000 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .30 in. to 125 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) X Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter .16 in. to 65 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface .12 in., weight 16.15 lbs./ft. Wall thickness or gauge No. 500 TYPE OF SCREEN OR PERFORATION MATERIAL: X PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot X3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 65 ft. to 125 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 125 ft., From ft. to ft. From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement X Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: None within 1/4 mile 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 2 Top Soil 2 15 Tan Medium Sand 15 30 Tan Clay mixed with Sand 30 45 Grey Clay 45 55 Grey Clay & Course Sand 55 123 Sand Medium to coarse Grey Sand & White Sand 123 125 Grey Clay								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/9/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 4/18/96 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peters								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								