

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	<u>SW 1/4 SW 1/4 NW 1/4</u>	<u>33</u>	T <u>23</u> S	R <u>3</u> E <u>(W)</u>

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>Gordon Schmidt</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>10320 N. Wheat State Rd.</u>	Application Number: <u>41874</u>
City, State, ZIP Code: <u>Inman, KS 67546</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>55</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered: <u>10</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: <u>10</u> ft. below land surface measured on mo/day/yr <u>6-8-96</u>
	Pump test data: Well water was <u>NA</u> ft. after hours pumping gpm
	Est. Yield gpm: Well water was <u>55</u> ft. after hours pumping gpm
	Bore Hole Diameter: <u>30</u> in. to <u>55</u> ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
Blank casing diameter: <u>16</u> in. to <u>30</u> ft., Dia			
Casing height above land surface: <u>12</u> in., weight <u>50</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>30</u> ft. to <u>55</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:			
From <u>20</u> ft. to <u>55</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet? <u>NA</u>				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	10	Brown Clay			
10	15	Gray Clay			
15	45	Medium Sand & Gravel			
45	55	Medium Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-8-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>537</u> This Water Well Record was completed on (mo/day/yr) <u>6-30-96</u> under the business name of <u>Flowers Drilling &amp; Pump Service</u> by (signature) <u>Mike Flowers</u>
---