

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		SW 1/4 NE 1/4 SE 1/4	22	T 23 S	R 3 E N
Distance and direction from nearest town or city street address of well if located within city? 2 miles East 1/4 North of Burrton, KS					
2 WATER WELL OWNER: John Weber		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 9414 W. 1st		Application Number: 14844			
City, State, ZIP Code: Halstead, KS 67056					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 240 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 39 ft. below land surface measured on mo/day/yr 2-15-97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 28 in. to 240 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 16 in. to 160 ft. Dia.		7 Fiberglass		Threaded	
Casing height above land surface 12 in. weight Sch 40 lbs./ft. Wall thickness or gauge No. 500					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement		11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot		5 Gauzed wrapped		8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched		6 Wire wrapped		9 Drilled holes	
		7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 160 ft. to 240 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 240 ft. to 20 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 20 ft. to 0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy		10 Livestock pens 14 Abandoned water well		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon		11 Fuel storage 12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage		None	
Direction from well? N/A		How many feet? N/A			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	8	Clay			
8	17	Sand + Gravel			
17	22	Tan Clay			
22	29 1/2	Like green clay			
29 1/2	60	Sand + gravel mixed with clay			
60	80	Sand + gravel			
80	85	Sand + gravel with clay			
85	90	Sand			
90	115	Equus Sand with clay			
115	140	Equus Sand			
140	153	Clay with soft gravel			
153	156	Clay			
156	170	Clay + sand			
170	240	Sand + gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-2-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 3-28-97 under the business name of Rosencrantz-Bemis Ent Inc by (signature) Alicia K. Coffey					