

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SE 1/4 NW 1/4		Section Number 17		Township Number T 23 S		Range Number R 3	
County: Harvey									
Distance and direction from nearest town or city street address of well if located within city? 1/2 mi W, 1 1/2 N of Burton									
2 WATER WELL OWNER:		Calvin Polk 7 Edgemore Hutch, KS 67501							
RR#, St. Address, Box #		Board of Agriculture, Division of Water Resources							
City, State, ZIP Code		Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 5 ft. below land surface measured on mo/day/yr 7-24-90 Pump test data: Well water was 7 ft. after 1 hours pumping 30 gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 40 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded							
2 PVC 4 ABS 7 Fiberglass		Threaded							
Blank casing diameter 6 in. to 13 ft., Dia 6 in. to 30 ft., Dia		Type of Screen or Perforation Material: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)							
Blank casing height above land surface 12 in., weight 3.25 lbs./ft. Wall thickness or gauge No. 16.0		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 13 ft. to 24 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 10 ft. to 40 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.							
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Pond		Direction from well? E How many feet? 30							
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS							
0 2 F Sand									
2 10 Gr + Gr Clay									
10 14 Rusty Sand + Gravel									
14 23 Sand + Gravel									
23 40 Gray Clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-24-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 11-4-90 under the business name of Miller Drilling by (signature) E Miller									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									