

1 LOCATION OF WATER WELL: County: Harvey Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 20 Township Number T 23 S Range Number R 3 EW

Distance and direction from nearest town or city street address of well if located within city? 130' N of SW Cor. of Harvey Ave & Highway 50

2 WATER WELL OWNER: Mr. Gilbert Hensley RR#, St. Address, Box #: Box 287 City, State, ZIP Code: Burrton, KS 67020 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Section Box Diagram] 4 DEPTH OF COMPLETED WELL: 18.0 ft. ELEVATION: NA Depth(s) Groundwater Encountered: 12.8 ft. WELL'S STATIC WATER LEVEL: 12.68 ft. below land surface measured on mo/day/yr: 3-11-94 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter: 8 in. to ... ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush Blank casing diameter: 2 in. to ... ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft., Dia. Casing height above land surface: flush in., weight: 7.03 lbs./ft. Wall thickness or gauge No. 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 18 ft. to 8 ft. From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 18 ft. to 7 ft. From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other Grout Intervals: From 7 ft. to 2 ft. From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NA Direction from well? NA How many feet? NA

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	Topsoil			
1.5	4.0	Clay			
4.0	6.0	Sandy, fine grain			
6.0	18.0	Sand, coarse-very coarse grain, w/gravel			
Flashmount waiver granted on 12-22-93 for Hensley Oil Co., Burrton, KS by Don Taylor					
5-31-94 Allison Irwin contacted Don Taylor regarding late forms					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 631 This Water Well Record was completed on (mo/day/yr) 5-31-94 under the business name of GSI by (signature) Brenda L. Irwin