


1 LOCATION OF WATER WELL:		Fraction <u>NW</u>	Section Number <u>29</u>	Township Number <u>T 23 S</u>	Range Number <u>R 3 E/W</u>
County: <u>Harvey</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>SE Cor. of Harvey Ave. & Highway 50</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>18.0</u> ft. ELEVATION: <u>NA</u>			
		Depth(s) Groundwater Encountered <u>13.2</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>13.3</u> ft. below land surface measured on mo/day/yr <u>3-11-94</u>			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter <u>8</u> in. to . ft. and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes . No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes . No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . Clamped .			
1 Steel		5 Wrought iron			
2 <u>PVC</u>		6 Asbestos-Cement			
3 RMP (SR)		7 Fiberglass			
4 ABS		8 Concrete tile			
Blank casing diameter <u>2 1/2</u> in. to . ft., Dia . in. to . ft., Dia . in. to . ft.		9 Other (specify below)			
Casing height above land surface <u>Flush</u> in, weight <u>703</u> lbs./ft. Wall thickness or gauge No. <u>154</u>		Welded .			
TYPE OF SCREEN OR PERFORATION MATERIAL:		Threaded <u>Flush</u>			
1 Steel		7 <u>PVC</u>			
2 Brass		8 RMP (SR)			
3 Stainless steel		9 ABS			
4 Galvanized steel		10 Asbestos-cement			
5 Fiberglass		11 Other (specify)			
6 Concrete tile		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot		9 Drilled holes			
2 Louvered shutter		10 Other (specify)			
3 <u>Mill slot</u>					
4 Key punched					
SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>8</u> ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>7</u> ft., From . ft. to . ft.					

6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 <u>Bentonite</u>		4 Other	
Grout Intervals: From <u>7</u> ft. to <u>2</u> ft., From . ft. to . ft., From . ft. to . ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
Direction from well? <u>NA</u>						13 Insecticide storage		<u>NA NA</u>	
						How many feet? <u>NA</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Fill			
3	6	Clay			
6	8	Sand, fine grain			
8	18	Sand, coarse-very coarse grain w/gravel			
Flushmount waiver granted on 12-22-93 for Hensley Oil Co., Burrton, KS by Don Taylor 5-31-94 - Allison Irwin contacted Don Taylor regarding late forms					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-9-94</u> and this record is true to the best of my knowledge and belief, Kansas	
Water Well Contractor's License No. <u>531</u>	This Water Well Record was completed on (mo/day/yr) <u>5-31-94</u>
under the business name of <u>GSI</u>	by (signature) <u>Brenda K. Hemmerson</u>