

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Harvey		NE 1/4 NW 1/4 NE 1/4	35	T 23 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city?					
2 3/4 mi E of the S edge of Burrton					
2] WATER WELL OWNER: Jack Welch					
RR#, St. Address, Box #: 326 Spruce					
City, State, ZIP Code: Halstead, KS 67056					
Board of Agriculture, Division of Water Resources					
Application Number:					
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF CASING USED: 55 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 24 ft. 2. 5-18-84 ft. 3. 20 ft.			
		WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 5-18-84			
		Pump test data: Well water was 28 ft. after 1 hours pumping 20 gpm			
		Est. Yield 50 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to 64 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Stock			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5] TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 6 in. to 45 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 12 in., weight 3.25 lbs./ft. Wall thickness or gauge No. 160					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 45 ft. to 55 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 40 ft. to 55 ft., From ft. to ft.					
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? E How many feet? 60					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 8 Br Sandy Silt					
8 21 Sand + Gravel					
21 34 Br Sandy Silt					
34 46 F Br Sand					
46 64 Sand + Gravel					
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-21-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 10-10-84 under the business name of Miller Drilling by (signature) Egan Miller					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					