| 1 LOCATION County:HARVE | OF WATER WELL: | Fraction SW 1/4 NW 1/4 SW 1/4 | | Number | Township Number 23 SOUTH | Range Number 3 WEST |
|--|---|--|---|--|--|--|
| Distance and d | irection from nearest to | own or city street address of well if RTH AND 90 FEET EAST OF PRAI | located within cit | y? D AND SW | / 36TH INTERSECTION | |
| WATER WELL OWNER: EQUUS BEDS GROUNDWATER MANAGEMENT DISTRICT RR#, St. Address, Box #: 313 SPRUCE STREET Board of Agriculture, Division of Water Resources City, State, ZIP Code HALSTEAD, KS 67056 Application Number: N/A | | | | | | |
| 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL 40 feet ELEVATION: feet WITH AN "X" IN SECTION BOX: Depth Groundwater Encountered 1 feet 2 feet 3 feet | | | | | | |
| w | N E | WELL'S STATIC WATER LEVE Pump test data: Estimated Yield gpn Bore Hole Diameter 6.0 i WELL WATER IS USED AS: | Well water w n: Well water w nch to 42 feet | as as f and | eet after hrs p inch to feet | oumping gpm umping gpm |
| | * | 1 Domestic 3 Feedle 2 Irrigation 4 Indust | ot | ublic water il field wate iwn and ga | rsupply 🔲 9 Dewat | tering 12 Other (specify below) oring well EB8A |
| Was a chemical/bacteriological sample submitted to Department? NO; If yes, when mm/dd/yy sample was submitted Water Well Disinfected? NO | | | | | | |
| 5 TYPE OF BLANK CASING USED: ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS ☒ Glued ☐ Clamped ☐ 1 Steel ☐ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded ☐ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass ☐ ☒ Threaded | | | | | | |
| Blank casing diameter STEEL 2 inches to 7.0 feet, Diameter PVC 2 inches to 30 feet, Diameter in to feet Casing height ABOVE land surface 36 inches, weight pounds/foot Wall thickness or gauge No | | | | | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | | | | | |
| SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed Wrapped 8 Saw Cut 11 None (open hole) | | | | | | |
| 2 Louvered shutter 4 Key Punched 7 Torch cut 10 Other (specify) | | | | | | |
| SCREEN-PERFORATED INTERVALS: From 40 feet to 30 feet, From feet to feet From feet to feet to feet GRAVEL PACK INTERVALS: From 42 feet to 25 feet, From feet to feet | | | | | | |
| GRAVEL PACK INTERVALS: From 42 feet to 25 feet, From feet to feet From feet to feet to feet to feet | | | | | | |
| 6 GROUT MATERIAL: 1 Neat cement | | | | | | |
| What is the nearest source of possible contamination: | | | | | | |
| ☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 12 Fertilizer storage ☐ 16 Other (specify below) | | | | | | |
| ☐ 3 Watertight sewer line ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 13 Insecticide storage Direction from well? SOUTH How many feet? 700 | | | | | | |
| FROM | TO | LITHOLOGIC LOG | FROM | TO | DI LIT | HOLOGIC LOG |
| 0.0 3 | LOAM, bi | | | | | |
| 3.0 9 | CLAY, gr | | | | | |
| 9.0 23 23 25 | | n, medium to coarse | | | <u> </u> | |
| 25 40 | | n, medium to coarse | | | | |
| 40 42 | . , | | | | | |
| | 0_11, 00 | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| 7 OVANIED | S CERTIFICATION: | This water well was eastern | atod on 44/49/ | 10(mo/do: | Aug Dunder my juris | diction and this record is true to |
| the best of m | o centification: Iv knowledge and be | I his water well was constructed. This Water Well Records to District No. 2 Kansas Water | avascampian | 4 VU 5/8 | nygai viluei iliy julis 01 (mo/day/yean) undo | diction and this record is true to er the business name of Equus |

(Signature and Title)