1 LOCAT		TER WELL:	Fraction SW 1/4 NW	1/4 SW 1/4	Section 34	Number	Township Number 23 SOUTH	Range Number 3 WEST	
Distance and direction from nearest town or city street address of well if located within city?  EB8B IS LOCATED 1760 FEET NORTH AND 90 FEET EAST OF PRAIRIE LAKE ROAD AND SW 36TH INTERSECTION									
2 WATER WELL OWNER: EQUUS BEDS GROUNDWATER MANAGEMENT DISTRICT									
RR#, St. Address, Box #: 313 SPRUCE STREET  City, State, ZIP Code HALSTEAD, KS 67056  RR#ANAGEMENT DISTRICT  Board of Agriculture, Division of Water Resources  Application Number: N/A									
	TE WELL'S I			OMPLETED WELL			ELEVATIO		
ANITHAN	X IN SE	CTION BOX:	·	Depth Groundwater Encountered 1 feet 2 feet 3 feet					
N WELL'S STATIC WATER LEVEL 13.68 feet below land surface measured on 11/30/00 mo/day/yr Pump test data: Well water was feet after hrs pumping gp									
			Estimated Yield gpm: Well water was feet after hrs pumping gpm  Bore Hole Diameter 6.0 inch to 160 feet and inch to feet						
	w	E	WELL WATER IS			ublic water		nditioning⊡11 Injection	
	X		☐ 1 Domestic☐ 2 Irrigation	☐ 3 Feedlot ☐ 4 Industrial		il field wate iwn and ga		tering	
Was a chemical/bacteriological sample submitted to Department? NO ; If yes, when mm/dd/yy sample was submitted Water Well Disinfected? NO									
S ' ' ' '									
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped  \[ \text{Algorithms} \] 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  \[ \text{Algorithms} \] 2 PVC 4 ABS 7 Fiberglass  Blank casing diameter STEEL 2 inches to 7.0 feet, Diameter PVC 2 inches to 145 feet, Diameter in to feet									
Casing height ABOVE land surface 36 inches, weight pounds/foot Wall thickness or gauge No									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
□ 1 Steel □ 3 Stainless steel □ 5 Fiberglass □ 8 RMP (SR) □ 11 Other (specify									
□ 2 Brass       □ 4 Galvanized steel       □ 6 Concrete tile       □ 9 ABS       □ 12 None used (open hole)         SCREEN OR PERFORATION OPENINGS ARE:       □ 5 Gauzed Wrapped       □ 8 Saw Cut       □ 11 None (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed Wrapped 8 Saw Cut 11 None (open hole) 1 Continuous Slot 3 Mill Slot 6 Wire Wrapped 9 Drilled holes									
2 Louvered shutter 4 Key Punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 155 feet to 145 feet, From feet to feet									
From feet to feet, From feet to feet GRAVEL PACK INTERVALS: From 160 feet to 140 feet, From feet to feet From feet to feet, From feet to feet									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout S 3 Bentonite S 4 Other									
Grout Intervals: From 2) 140 feet to 12 feet, From 3) 12 feet to 0 feet, From feet to feet									
What is the nearest source of possible contamination:									
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 11 Fuel storage ☐ 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
☐ 3 Watertight sewer line ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 13 Insecticide storage  Direction from well? SOUTH How many feet? 700									
FROM	TO TO	SOOTH HO	LITHOLOGIC LO	)G	FROM	т т	DI LIT	HOLOGIC LOG	
0.0	3	LOAM, b	rown						
3.0	9	CLAY, gr							
9.0	23		n, medium to	coarse					
23	25	CLAY, ta							
25	40	,	n, medium to	coarse					
40	82		n, caliche 55'						
82	95		in, medium to						
95	103	CLAY, da		Coarse					
103	153		n-gray, medi	····					
153	160			uiii					
100	100	CLAY, gr	<u>ay</u>						
7 OVANICOUS OFFICIATION. This was well as a second of the									
الح. OWNER'S CERTIFICATION: This water well was constructed on 11/21/00(mo/day/year under my jurisdiction and this record is true to the best of my knowledge and belief. This Water Well Record was completed on 2/8/01(mo/day/year) under the business name of Equus									
Beds Groundwater Management District No. 2. Kansas Water Well License No. not applicable.									
	The Na								
(Signature and Title)									