				_				
1 LOCATION OF W County:HARVEY	ATER WELL:	Fraction SE 1/4 SE 1/4	SE 1/4	Section 34	Number	Township Number 23 SOUTH	Range Number 3 WEST	
Distance and direction from nearest town or city street address of well if located within city? EB 14 A - From Intersection of US 50 and BurMac Rd 2 miles south and 2 mile east								
2 WATER WELL OWNER: Equus Beds Groundwater Management District								
RR#, St. Address, Box #: 313 Spruce Street Board of Agriculture, Division of Water Resources City, State, ZIP Code Halstead Kansas 67056-1925 Application Number: NA								
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL 40.0 feet ELEVATION: UNK feet WITH AN "X" IN SECTION BOX: Depth Groundwater Encountered 1 19.79 feet 2 feet 3 feet								
N WELL'S STATIC WATER LEVEL 19.79 feet below land surface measured on 11/27/00 mo/day/yr								
w	E	Pump test data: Well water was feet after hrs pumping gpm Estimated Yield 9.5 gpm: Well water was feet after hrs pumping gpm Bore Hole Diameter 6.0 inch to 42.0 feet and inch to feet WELL WATER IS USED AS: 5 Public water supply 8 Air conditioning 11 Injection						
		☐ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☑ 10 Monitoring well. EB 14 A						
-	I mile	Was a chemical/bacteriological sample submitted to Department? NO; If yes, when mm/dd/yy sample was submitted Water Well Disinfected? NO						
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter Steel 2.0 inches to 7.0 feet, Diameter PVC 2.0 inches to 30.0 feet, Diameter in to Casing height ABOVE land surface 33.6 inches, weight pounds/foot Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed Wrapped 8 Saw Cut 11 None (open hole)								
☐ 1 Continuous Slot 3 Mill Slot 6 Wire Wrapped 9 Drilled holes 2 Louvered shutter 4 Key Punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 40.0 feet to 30.0 feet. From feet to feet								
From feet to feet, From feet to feet								
GRAVEL PACK INTERVALS: From 40.0 feet to 27.0 feet, From feet to feet From feet to feet to feet								
6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☑ 4 Other ☐ —————								
Grout Intervals: From27.0 feet to 0.0 feet , From feet to feet , From feet to feet								
What is the nearest source of possible contamination: ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 11 Fuel storage ☐ 15 Oil well/Gas well								
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 12 Fertilizer storage ☐ 16 Other (specify below)								
☐ 3 Watertight sewer line ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 13 Insecticide storage Road Ditch								
Direction from well? SOUTH How many feet? 20.0 FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG								
0.0 9.0	CLAY, b	LITHOLOGIC LOG		FROM	10) LIII	HOLOGIC LOG	
9.0 40.0								
		nedium to coars	-					
40.0 42.0	CLAY, g	ray						
	<u> </u>							
	Ī							
	1							
	.					<u> </u>		
the best of my knowledge and belief. This Water Well Record was completed on 2/12/01(mo/day/year) under the business name of Equus								
Beds Groundwater Management District No. 2. Kansas Water Well License No. not applicable.								
(Signature and Title)								