MW-04	NA/A	TED WELL DECORD	\454C				
1 LOCATION OF WAT	ER WELL: Fraction	_	Form WWC-	5 KSA 82 ction Number		Number	Range Number
County: HARVE	7	14 NW 14 NV	1/4	21	T Z		R 3 EW
	from nearest town or city stree	t address of well if located	within city?				<u> </u>
106 SOUTH	BURMAC RD	(1 M: NORTH	OF BO	MRTUN	<u>/</u> )		
2 WATER WELL OW	NER: ED CLEMENT,	W/ AQUECA, Z	NC.				
RR#, St. Address, Box	# : 10700 FAST 3	50 HWY, PO A	30 K 119	739	Board of	Agriculture, I	Division of Water Resource
City, State, ZIP Code	: KANSAS CIT	4, MO 64	138		Application	n Number:	
AN "X" IN SECTION	DCATION WITH 4 DEPTH OF	COMPLETED WELL	16.3	ft. ELEV	ATION:		
- <del>                                     </del>	Depth(s) Grou	ndwater Encountered 1.		イ・・・・・ ft.	2	ft. 3	ft.
	WELLSSIAI	TIC WATER LEVEL . 3	ν 3.	pelow land su	Ifface measured o	n mo/day/yr	mping . Q : Z <> gpm
NW	NE   Fst Yield	onm: Well water	was .4.	- π.	after . V 7.3	. hours pu	mping gpm mping gpm
	Bore Hole Dia	meter Tin to	1/0.3		anter	. nours pu	mping gpm . to
Mile W			Public water		8 Air conditioning		
	1 Domest		Oil field wa			=	Injection well Other (Specify below)
sw	SE 2 Irrigatio						(Specify below)
1  1  1	·						mo/day/yr sample was sub
<u> </u>	mitted				ater Well Disinfect		No No
5 TYPE OF BLANK C	ASING USED:	5 Wrought iron	8 Concr				I Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement		(specify belo			<u>ad</u>
2 PVC	4 ABS	7 Fiberglass				Threa	
Blank casing diameter .	in. to	O ft., Dia —	in. to		ft Dia	_	in to #
Casing height above lar	nd surfaceQ.aO	in., weight	• • • • • • • • • • • •	lbs	/ft. Wall thickness	or gauge No	SCHEDUCE 40
TYPE OF SCREEN OR	PERFORATION MATERIAL:		7 PV	(2)		pestos-ceme	
1 Steel	3 Stainless steel	5 Fiberglass		IP (SR)			···
2 Brass	4 Galvanized steel	6 Concrete tile	9 AB	s		ne used (op	
	ATION OPENINGS ARE:	5 Gauzeo	wrapped		8 Saw cut	V-F	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire w	apped		9 Drilled holes		(
2 Louvered shutte		7 Torch o			10 Other (specif	y)	
SCREEN-PERFORATE	D INTERVALS: From	6, 0 ft. to . /	6.4.0	ft., Fro	om <del></del>	ft. to	)
	From	ft. to . , .		ft., Fro	om <u></u>	ft. to	o
GRAVEL PAC	K INTERVALS: From	····· ft. to		ft., Fro	om	ft. to	) <del></del>
	From	ft. to		ft., Fro		ft. to	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bento	nite 4	Other		
Grout Intervals: From	3.0ft. to	From	ft.				. ft. to
	rce of possible contamination:			10 Lives	stock pens		andoned water well
	4 Lateral lines	7 Pit privy			storage	15 Oi	l well/Gas well
2 Sewer lines	5 Cess pool r lines 6 Seepage pit	8 Sewage lagoo	n		izer storage	16 Ot	her (specify below)
	Sout H	9 Feedyard			cticide storage		
FROM TO	LITHOLOGIC	2106	FDOM			£'+	
0 0.2	Gravelly SILT (		FROM	то	PI.	UGGING IN	ITERVALS
0.2 1.3	Fine SAND (S						
	DK brown , Silty (						
	dry	sonr cecy, stiff					
	Brown, Sindy SI	7 (M/)					
^	Brown / red-brown						
	SAND (SP)	71.0010					
CONTRACTOR'S OF	R LANDOWNER'S CERTIFICAT	FION: This water well was	// Construc	(2) reco	instructed or (2) =	luggedd-	r my luriodiation
completed on (mo/day/ye	ear)7-25-03	The state of the s	- Soristiae	and this reco	rd is true to the ho	iuggeu unde stof my kaai	or my jurisdiction and was wledge and belief. Kansas
Water Well Contractor's		This Water Well	Record was	Completed	on (mo/day/water	. A.	mouye and belief. Kansas ファ・フルユ
under the business name		NC		by (signat			~ ~ /· COV
INSTRUCTIONS: Use type	writer or ball point pen. PLEASE PRESS		fill in blanks			and too there	point to Konser Service
of Health and Environmen	t, Bureau of Water, Topeka, Kansas 666	20-0001. Telephone: 913-296-5545	Send one to V	VATER WELL OV	WIFE and retain one fo	and top trifee co	ppies to Narisas Department