WATER WELL RECORD Fo	rm WWC-5	KSA 82a-1212	ID No.	00157173
----------------------	----------	--------------	--------	----------

	N OF WATER	> W/E'II ·	Fraction				Conti	ion Nun	nhari Toumeni	n Number	Panas	Viimher !
County:		vey.		1/2 NN	N v	NE		29	1	p Number 3 S	Range I	3 EM
Distance and				et address	of well if	located w	ithin city?			- 3		- 50
Hensley O				01 444.000								
	VELL OWNER											
	ress, Box #								Board of A	Agriculture, Div	ision of Water	Resources
City State 7	IP Code	Burton	Ke 670	20						n Number:		1103001003
LOCATE	WELL'S LOC	ATON WITH	1, 10 010						Applicatio	ii iyumber.		
3 AN "X" IN	SECTION BO	OX:	4 DEPTH	OF COMPI	LETED	NELL	32	ft.	ELEVATION:	1	451.42	
	N		Depth(s) Gr	oundwater	Encoun	tered 1			ft. 2	ft.	3	ft.
A			WELL'S ST	ATIC WAT	ED I EV	E1	NA e i	holow le	and surface measu	red on molday	lur	
Ī	X		1									
 	-NW	NE							ft. after			
	i	•	Est. Yield	(gpm: \	Veli water	was		ft. after	hours	oumping	gpm
₹ w		E	Bore Hole D	Diameter	8	in. to	32		ft. and	ii	n. to	ft.
7			WELL WAT	ER TO BE	USED /	NS: 5 Pu	ıblic water su	ipply	8 Air con 9 Dewate	ditioning 1	1 Injection w	ell
	-sw -	SE	1	iestic 3	reed lot		i neid water s	suppiy	Dewate	enng 1	2 Other (Spe	icity below)
	i	i	2 Irrig						nestic) (10 Monit			
* <u></u>		<u>!</u>	Was a chen	nical/bacter	iologica	l sample s	ubmitted to D	epartm	ent? Yes N	o_X If yes	, mo/day/yr sa	ample was
	S		submitted						Water Well Disinf	fected? Yes	No	X
5 TYPE OF	BLANK CAS	ING USED:		5	Wrough	iron	8 Concre	ete tile	CASING	JOINTS: Glue	dCla	amped
Stee	el	3 RMP (SR)	6	Asbesto	s-Cement	9 Other (ied	
(2) _{PVC}	:	4 ARS		7	Eiharala					Thre	hahe	Y
Rlank casina	diameter	2	in to	30	ft Dia		in to	• · n	ft., Dia		in to	#
One in Casiliy	ulameter _		- "". "	·····	. II., Dia		716			N-	- "". 10	
Casing neign	it above land	surface		in., w	eignt		:/ .!.	DVO ID	s./π. vvaii tnicknes	s or gauge No.		134
1 YPE OF SC	KEEN OR P	ERFORATIO	N MATERIAL ess steel nized steel IGS ARE:	.: -	C:5!-		Ý	PVC	5R) 11	Aspestos-ceme	ent	
1 3100	31	3 Stainle	ess steel	5	Concessa	55 - 4:1-	0	ABS	or() 11 1	Other (specify) None used (op		
2 Bras	SS R PERFORAT	A Gaivar	nizea steei	0	Concret	e tile 5 Court	ed wrapped	ABS	Osaw art	None usea (op	en noie) 11 None (c	non hole)
	tinuous slot		Mili slot				vrapped		9 Drilled h		11 140118 (0	pen noie)
	vered shutter		Key punche	d		7 Torch			10 Other (s			
	RFORATED								ft. From	ροσιιγ,		
SCREEN-PE	RECKATED	IN I ERVALS:										
			From		¹¹	. to			ft. From	π.	to	π.
GRA	VEL PACK I	NTERVALS:	From	28			32		ft. From		to	ft.
					fi	. to			ft. From		to	ft.
6 GROUT	MATERIAL:		cement				3 Bent	tonite	4 Other			
Grout Interva	als From	2	ft. to	28 ft	. From		ft. t	0	ft. Fro	m	ft. to	ft.
	nearest source								Livestock pens	14 At	andoned wat	er well
	tic tank		4 Lateral		7	Pit privy			Fuel storage	15 Oi	well/ Gas we	ell .
•	er lines		5 Cess po				lagoon		Fertilizer storage		her (specify b	
	ertight sewer		6 Seepag			Feedyan			Insecticide storage	<u>_</u>	ontaminat	
	ū	111103	o Geepag	e bir	9	i cc uyan	•					
Direction from FROM		CODE	1.1**	THOLOGIC	100		FROM	How	many feet?	PLUGGING I	NTERVAL S	
0	.5		ment	HOLOGIC	, 200		FICOIVI	+		. LOCGING I	TILLIANEO	
.5	10		ndy clay			·····	 	-				
10	32	l o	ose sand	L aray	ام							·
- 10	72	LO	Jupe serie	. G ylav	J1							
	·											
							-	+		<u> </u>		
								+				
							 	-				
								+				
								+				
							<u> </u>	-				
								-				
								+				
= 1001	CTOP'S OF	LANDONAINE	D'S CEDTIE	CATION	This wet	or well was	(1) construc	tod (2)	reconstructed, or (3	() plugged under	r my juriedicti	on and was
	O LOK S OK	PVIADOMAPE	ハマウロベニド	OATION:		ei meii mas	The strict	رکی, (۷)	reconstituced, or (3	n hindan mine	,, my junisuicu	O11 G11U WG5
				12 45 04	1				.d != 4 4	4 - £ 1 1-		6 Van
completed o	n (mo/day/yr)		·	12-15-04					d is true to the bes	•	dge and belie	
completed o	n (mo/day/yr) Contractor's L				4		This W		rd is true to the bes /ell Record was con by (signature)	•	dge and belie	f. Kansas 4-01-04