	WATER WE	LL RECORD For	m WWC-5	KSA 82a-12	12 ID No. RRW	/3ME2 (s)	
1 LOCATION OF WATER WELL:	Fraction			on Number	Township Numbe		•
County: Harvey Distance and direction from nearest town	NE 1/4 N	of well if located w	thin city?	25	т 23	S R	3 w
51.5 Feet south of center of Hwy.				e Road			
2 WATER WELL OWNER: City of V							
RR#, St. Address, Box # : 6016 So					Board of Agriculture	e, Division of Wat	er Resources
City, State, ZIP Code : Halstead	i, Kansas 6705	6			Application Numbe	r:	
3 LOCATE WELL'S LOCATON WITH 4 AN "X" IN SECTION BOX:	DEPTH OF COMP	LETED WELL	82	ft FLEVA	ATION:	1439	
N D	epth(s) Groundwater	Encountered 1	14	ft.	2	ft. 3	ft.
A X X	VELL'S STATIC WAT	ER LEVEL	14 ft. b	elow land su	rface measured on m	o/day/yr 9/	7/2006
					after h		
NW	st. Yield	gpm: Well water	was	ft.	after h	ours pumping	gpm
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ore Hole Diameter	8 " in. to	BZ	f	ft. and 8 Air conditioning 9 Dewatering	in. to	ft.
-	VELL WATER TO BE	USED AS: 5 Pu	blic water su	pply	8 Air conditioning	11 Injection	well
swse	2 Irrigation 4	reed lot 6 OI	we and garde	uppiy an (domostic)	Monitoring well	iz Other (Sp	echy below)
 					es No X		
	ubmitted	giodi sampie si			er Well Disinfected?		lo X
5 TYPE OF BLANK CASING USED:		Wrought Iron	8 Concre		CASING JOINTS:		
						Welded	
OPVC 4 ABS	7					Threaded	X
Blank casing diameter 2	n. to 72	ft Dia	in. to	1	ft Dia	in. to	ft.
Casing height above land surface TYPE OF SCREEN OR PERFORATION I Steel 3 Stainless 2 Brass 4 Galvaniz	32 in., w	eight	0.68	lbs./ft. V	Vall thickness or gaug	je No. Se	h. 40
TYPE OF SCREEN OR PERFORATION I	MATERIAL:		(J)	PVC	10 Asbestos	-cement	
1 Steel 3 Stainless	s steel 5	Fiberglass	8 F	RMP (SR)	11 Other (sp	ecify)	
SCREEN OR PERFORATION OPENING	S ARE:	5 Gauze	d wrapped	400		11 None	open hole)
SCREEN OR PERFORATION OPENINGS 1 Continuous slot 2 Louvered shutter 4 Ke	ill slot	6 Wire w	rapped		9 Drilled holes		
	ey punched	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATED INTERVALS:				ft. Fr	om	ft. to	ft.
	From	ft. to		ft. Fr	om	ft. to	ft.
GRAVEL PACK INTERVALS:					om		
6 GROUT MATERIAL: 1 Neat cer	From	π. το	2.0	π. Fr	om Volciav	ff. to	ft.
Grout intervals From 0 ft.	to 70 ff	Erom	3 Bento	onite 4	# Erom	# to	4
What is the nearest source of possible cor		. FIOII	n. to	10 Livesto	ock pens 1	14 Ahandoned wa	iter well
	Lateral lines	7 Pit privy			orage 1		
2 Sewer lines 5				12 Fertiliz	er storage 1	16 Other (specify	below)
_	Seepage pit	9 Feedyard	l		cide storage		
Direction from well?	LITUOLOGIA	1.00	ED014	How many fo		INO INTERVALO	
FROM TO CODE	LITHOLOGIC	LUG	FROM	то	PLUGG	ING INTERVALS	
See	attached log		-				
			-	-			
		741.4					
		404	 				
7 CONTRACTOR'S OR LANDOWNER'S			_			,	1
completed on (mo/day/yr)	09/07/200	0			e to the best of my kr		
Water Well Contractor's License No.	10	tonean Carr	This Wa	ater Well Red	cord was completed or	mo/day/yr)	3/12/2006
under the business name of INSTRUCTIONS: Please fill in blanks a	ind circle the correct an	stensen Comp	opies to Kansa	by as Department	(signature) (Signature) of Health and Environment	ent. Bureau of Wate	er 1000 S W
Jackson St., Ste. 420, Topeka, Kansas 6	6612-1367. Telephone	e: 913-296-5545. Se	end one to WA	TER WELL O	WNER and retain one fo	or your records.	

TEST HOLE REPORT

LAYNE Western, a Div. of LAYNE Christensen Wichita, Kansas

Contrac	Name:	Wichita ASR	Test Hole No.	RRW3 ME2 (s)		
			Date:	SEPT 7,2006		
		19	Driller:	KEVIN HOLUB		
Location of Test Hole:		Elevation of T	Elevation of Test Hole:			
			Static Water L	Static Water Level:		
Page 1			Measured	Hours After Completion		
From	То		Description of Str	ata		
0	5	brown sandy silty cla	y clay, medium plastic			
5	10	brown, orange sandy silty clay, medium plastic				
10	15	orange, gray silty sand, fine to coarse, clay lens				
15	20	orange, gray sandy silty clay, medium plastic, sand lens				
20	25	orange, gray silty clayey sand, fine to coarse, medium plastic				
25	30	orange, gray sandy silty clay, medium plastic				
30	35	orange, gray silty clayey sand, fine to coarse, medium plastic				
35	40	olive, gray, orange silty clay, medium to high plastic				
40	45	olive, gray, orange silty clay, medium to high plastic, slight sand				
45	50	olive, gray, orange sandy silty clay, medium to high plastic				
50	55	olive, gray silty clay, high plastic				
55	60	olive, gray, orange silty sand, fine to medium, clay lens				
60	65	olive, gray, orange silty sand, fine to coarse, clay lens				
65	70	orange silty sand, fine to coarse with gravel				
70	75	orange silty sand, fine to coarse with gravel				
75	80	orange silty sand, fine to coarse with gravel				
80	85	orange silty sand, fine to coarse with gravel, clay lens				