

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	Near $\frac{1}{4}$ Center $\frac{1}{4}$ SW $\frac{1}{4}$	13	T 23 S	R 3

Distance and direction from nearest town or city street address of well if located within city?

3 miles East &amp; 1 1/4 Mile North of Burrton

2 WATER WELL OWNER: John Weber	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 9414 W. 1st	Application Number: 41,341
City, State, ZIP Code: Halstead, KS 67056	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL... 140 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1... 37.6" ft. 2... ft. 3... ft.
	WELL'S STATIC WATER LEVEL 37.6" ft. below land surface measured on mo/day/yr 11-11-94
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 1000 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 3.0 in. to 1.41 ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 1.6 in. to 1.00 ft., Dia			Threaded
Casing height above land surface 12 in., weight 16.15 lbs./ft. Wall thickness or gauge No. 500			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	11 None (open hole)
2 Louvered shutter	4 Key punched	7 Torch cut	9 Drilled holes
SCREEN-PERFORATED INTERVALS:		10 Other (specify)	
From 1.00 ft. to 1.40 ft., From			
From ft. to ft., From			
GRAVEL PACK INTERVALS:			
From 20 ft. to 1.40 ft., From			
From ft. to ft., From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From				
What is the nearest source of possible contamination: None within 1/2 mile		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Fine Sandy Soil			
5	10	Brown Clay			
10	31	Medium Red Sand			
31	48	Gray Clay			
48	64	Gray Sandy Clay			
64	82	Medium to Course Sand-Gray			
82	85	Green Clay			
85	94	Gray Clay			
94	113	Fine to Medium Sand-Tan			
113	115	Gray Clay			
115	121	Fine to Medium Sand-Tan			
121	122	Gray Clay			
122	139	Fine to Medium Sand-Tan			
139	141	Gray Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-11-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 11-23-94 under the business name of Peterson Irrigation Inc. by signature Mike Peterson
--