

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>		Near Center $\frac{1}{4}$ NE $\frac{1}{4}$	23	T 23 S	R 3
Distance and direction from nearest town or city street address of well if located within city? <u>3 Miles East & 3/4 North of Burrton, KS</u>					
2 WATER WELL OWNER: <u>John Weber</u>					
RR#, St. Address, Box # : <u>9414 W. 1st</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Halstead, KS 67056</u>			Application Number: <u>41,342</u>		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>134</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>19.6"</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>19.6"</u> ft. below land surface measured on mo/day/yr <u>11-15-94</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>1,000</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>30</u> in. to <u>134</u> ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter <u>16</u> in. to <u>75</u> ft., Dia <u>86</u> in. to <u>95</u> ft., Dia <u>124</u> in. to <u>134</u> ft.		CASING JOINTS: Glued <u>X</u> Clamped			
Casing height above land surface <u>12</u> in., weight <u>16.15</u> lbs./ft. Wall thickness or gauge No. <u>500</u>		Welded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		Threaded			
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				7 PVC	
				8 RMP (SR)	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		3 Mill slot		8 Saw cut	
2 Louvered shutter		4 Key punched		11 None (open hole)	
				6 Wire wrapped	
				9 Drilled holes	
				7 Torch cut	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From <u>75</u> ft. to <u>86</u> ft., From ft. to ft.			
		From <u>95</u> ft. to <u>124</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>20</u> ft. to <u>134</u> ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other					
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: <u>None within 1/2 Mile</u>					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Sandy Top Soil			
4	13	Brown Clay			
13	28	Medium Course Sand			
28	46	Brown Clay			
46	54	Light Gray Clay			
54	58	Fine Sand			
58	66	Gray Clay			
66	84	Fine to Medium Sand			
84	93	Green Clay			
93	106	Fine to Medium Sand			
106	109	Light Gray Clay			
109	122	Fine to Medium Sand			
122	124	Brown Clay			
124	134	Dark Gray Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-15-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>138</u> This Water Well Record was completed on (mo/day/yr) <u>11-23-94</u> under the business name of <u>Peterson Irrigation Inc.</u> by (signature) <u>Mike Peterson</u>					