

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County:	Harvey	SE ¼ NE ¼ NW ¼	29	T 23 S	R 3 W E/W	

Distance and direction from nearest town or city street address of well if located within city?

Corner of Blaine & Colorado

2	WATER WELL OWNER:	Bridgeman Oil, Co.	
	RR#, St. Address, Box # :	109 Clay	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Hutchinson, Kansas 67501	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1451 ft.

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 2/7/95

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield NA gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 20 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		12 Other (Specify below)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:			5 Wrought iron			8 Concrete tile			CASING JOINTS: Glued Clamped					
1 Steel			3 RMP (SR)			6 Asbestos-Cement			9 Other (specify below) Welded					
2 PVC			4 ABS			7 Fiberglass			Threaded. X					
Blank casing diameter 2 in. to 10 ft., Dia		 in. to ft., Dia		 in. to ft., Dia		 in. to ft.					
Casing height above land surface -1.8 in., weight lbs./ft.		 in., weight lbs./ft.		 in., weight lbs./ft.			Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:														
1 Steel			3 Stainless steel			5 Fiberglass			7 PVC			10 Asbestos-cement		
2 Brass			4 Galvanized steel			6 Concrete tile			8 RMP (SR)			11 Other (specify)		
									9 ABS			12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:														
1 Continuous slot			3 Mill slot			5 Gauzed wrapped			8 Saw cut			11 None (open hole)		
2 Louvered shutter			4 Key punched			6 Wire wrapped			9 Drilled holes					
						7 Torch cut			10 Other (specify)					
SCREEN-PERFORATED INTERVALS:														
From 10 ft. to 20 ft., From ft. to ft.			From ft. to ft., From ft. to ft.			From ft. to ft., From ft. to ft.			From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS:														
From 8 ft. to 10 ft., From ft. to ft.			From ft. to ft., From ft. to ft.			From ft. to ft., From ft. to ft.			From ft. to ft., From ft. to ft.					

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 6 Other (specify below)
13 Insecticide storage Former UST ba.....
Direction from well? NE How many feet? 80

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-27-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 36893
under the business name of GeoCore Services, Inc. This Water Well Record was completed on (mo/day/yr) 3-6-95
by (signature) Dale Hall