					86	elly.	# /		
WATER	R WEL	L RECORD	Form W	WC-5	D	oivision of Wate	r Resources App. N	10. 2011/0345	
•		OF WATER WELL:	Fraction C 14 NE	4. NF.	Secti	ion Number	l ownship No.	Range Number	
Street/Rural Address of Well Location; if unknown, distance & direction						25 T 23 (S) R 30 DE WW Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .						Latitude: (in decimal degrees)			
Garden City: 16 1/2 miles E/NE on 156 2 South						Longitude: (in decimal degrees)			
						Elevation:			
2 WATER WELL OWNER: Hess Oil Co						Collection Method:			
RR#, Street Address, Box #: City, State, ZIP Code : McDhorgon KS 67460						☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
McPherson KS 67460						Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCA		LL 4 DEPTH OF 4	COMDITTED WELL	r 200		£.			
WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1) 5.5 ft. (2) ft. (3) ft. (3) ft. (3) ft. (4) WELL'S STATIC WATER LEVEL 5.5 ft. (below land surface measured on mo/day/yr								(3) ft.	
N WELL'S STATIC WATER LEVEL 8.5ft. below land surface measured on m							neasured on mo/	day/yr8=18=1/	
Pump test data: Well water was									
NW NE EST. YIELD Dgpm. well water was									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No If yes, mo/day/yr sample was submitted									
Water well disinfected? 🙀 Yes 🗌 No									
		SING USED:					••••		
CASING JOINTS: X Glued Clamped Welded Threaded									
Casing diameter									
Casing height above land surface24									
Steel Stainless Steel PVC Other (Specify)									
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify)									
From									
	GRAVEL PACK INTERVALS: From50								
6 CPOI	TT MAT	TERIAL: X Neat ceme	From	ft. to	nita I	ft., From	ft	. to ft.	
Grout Int		From1 ft. to	25 ft., From)]	. ft. to	ft.,	±⊖∙р±ид ·····	ft. toft.	
What is the nearest source of possible contamination:									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock per ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage									
	nt sewer lines	it Feedyard	Fertilizer storage Oil well/gas well						
		n well South				vell	350	HOODIG DITERVALG	
FROM	TO	LITHOLOG		FROM	TO	LITHO. L	OG (cont.) or PL	UGGING INTERVALS	
0	3 14	Topsoil Clay							
14	30	Caliche clay							
30	52	Tan clay							
52	64	Medium sand							
64 97	97 128	Sand Sandstone and s	andy clay						
128	138	Tan sandy clay							
138	200	Blue clay							
300 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 11 12 200 310 310 11 12 200 310 310 310 310 310 310 310 310 310 3									
under my jurisdiction and was completed on (mo/day/year) 2.28									
Kansas Water Well Contractor's License Nowcci, 430 This Water Well Record was completed (molday/year) 2 2.8 1.1.									
under the business name of Howard Drilling Box 806 Beaver OK 7398 Isignature)									
(white, blu	e, pink) to	Kansas Department of Health	and Environment, Bureau	of Water, Geo	logy Secti	ion, 1000 SW Ja	ckson St., Suite 420,	, Topeka, Kansas 66612-1367.	
		5524. Send one copy to WAT ov/waterwell/index.html.	ER WELL OWNER and	retain one for	your reco	ords. Include fe	e of \$5.00 for each	constructed well. Visit us at	
KSA 82a-									