WATE	R WEI	LL RECORD	Form V	VWC-5	Di	vision of Wate	r Resources App. No	24,582		
		OF WATER WELL:	Fraction			on Number	Township No.	Range Num	ber	
Coun	ity: Finr	nev	1/4 SW 1/4 SI			36	T 23 S	R 34	]E <b>⊘</b> W	
Stree	t/Rural A	Address of Well Location; i	f unknown, distance		Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here .						Latitude: (in decimal degrees)				
From Holcomb,1mile North 2740' N. 1220' W.						Longitude: (in decimal degrees)				
						Elevation:				
2 WATER WELL OWNER: Small Seven c/o Ron Pettz						Collection Method:				
RR#, Street Address, Box #: P.O. Box 155						GPS unit (Make/Model:)				
City, State, ZIP Code : Deerfield, KS. 67838						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
			······································		Est. A	ccuracy: \( <	3 m, 🔲 3-5 m, 🔲	5-15 m, ∐ >	15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 345 ft. ft.										
	WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)									
J. SEC.	N WELL'S STATIC WATER LEVEL151									
Pump test data: Well water wasft. after hours pumping gpm										
EST VIELD gpm. Well water was ft. after hours pumping gpm										
$ \mathbf{w} $   $ \mathbf{x} $   Bore Hole Diameter 39										
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well										
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)										
Irrigation   Industrial   Domestic-lawn & garden   Monitoring well										
Was a chemical/bacteriological sample submitted to Department? Yes V No										
S If yes, mo/day/yr sample was submitted										
Water went disinfected: W 1 cs 1 10										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter .16 in. to .200 ft., Diameter ft., Diameter ft.										
Casing height above land surface12										
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Stainless Steel ☐ PVC ☐ Other (Specify)										
✓ Steel       ☐ Stainless Steel       ☐ PVC       ☐ Other (Specify)         ☐ Brass       ☐ Galvanized Steel       ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot   ☑ Mill slot   ☐ Gauze wrapped   ☐ Torch cut   ☐ Drilled holes   ☐ None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)										
SCREE	N-PERF									
			From	ft. to		ft., From	tt. t		ft.	
	GRAVI	EL PACK INTERVALS:								
( CRO)	TIOC NA AO	ΓERIAL:	From	II. 10		. II., From	IL. I	.0	It.	
		From .0 ft. to								
Grout In		est source of possible contains			11. 10	11.,	rioiii	. 11. 10		
	Septic tar		es Pit privy	Livestock	pens !	Insecticide	storage	er (specify belo	w)	
Sewer lines Cesspool Sewage lagoon Fuel storage 🗹 Abandoned water well									,	
	Watertigh	nt sewer lines		Fertilizer s		Oil well/ga				
					~		h . 90' East			
FROM	TO	LITHOLOGI	IC LOG	FROM	TO	LITHO, LC	OG (cont.) or PLU	GGING INTE	ERVALS	
	· · · · · ·			1				,		
				<del>                                     </del>		<del>.</del>	· · · · · · · · · · · · · · · · · · ·			
		Coo Attorbad Lar		+						
		See Attached Log		+						
				+		· · · · · · · · · · · · · · · · · · ·		<del></del>	<del>,</del>	
				<del> </del>						
	-			+						
	-									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year) .8-25-10 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 9-1-10										
under the	e busines	s name of Minter Wilson	n Drilling Co. Inc.		by (si	gnature) ${\cal C}$	ala Bakken.	,		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies										
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										

## The Professionals MINTER-WILSON DRILLING CO.

Irrigation and Domestic **Water Systems** Complete Installation and Repairing

## **INCORPORATED**

P.O. Box A • **GARDEN CITY, KANSAS 67846** Phone 620-276-8269

NAME

SMALL SEVEN

**RON PETTZ - TENANT** 

COUNTY

FINNEY

DATE

8-14-10

LOCATION:

NE 1/4 36-23-34 - HWY. 50 & LOWE ROAD - 1/2 MILE NORTH

& 1/4 MILE WEST

88 FT. WEST & 45 FT. NORTH OF

EXISTING WELL

STATIC WATER LEVEL - 160 FT.

## TEST#2

0' TO 19' - BROWN CLAY

19' TO 22' - GRAY CLAY

22' TO 26' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

26' TO 33' - GRAY CLAY

33' TO 42' - BROWN CLAY SANDY

42' TO 60' - BROWN CLAY WITH STRIPS OF WHITE ROCK

60' TO 74' - BROWN SANDY CLAY

74' TO 79' - FINE TO MEDIUM SAND & GRAVEL

79' TO 83' - BROWN CLAY

83' TO 127' - BROWN SANDY CLAY

WITH STRIPS OF WHITE CLAY & WHITE ROCK

127' TO 131' - FINE TO MEDIUM SAND & GRAVEL

131' TO 143' - BROWN SANDY CLAY

WITH STRIPS OF WHITE CLAY & WHITE ROCK

143' TO 159' - BROWN SANDY CLAY

WITH STRIPS OF SAND & GRAVEL

159' TO 167' - FINE TO MEDIUM SAND & GRAVEL

167' TO 185' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY - 30%

185' TO 194' - FINE TO MEDIUM SAND & GRAVEL

194' TO 203' - BROWN SANDY CLAY

203' TO 228' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 15%

228' TO 233' - BROWN SANDY CLAY

233' TO 259' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 10%

259' TO 274' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

274' TO 283' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY & WHITE ROCK - 30%

283' TO 290' - BROWN SANDY CLAY

WITH STRIPS OF WHITE ROCK & SAND & GRAVEL - 40%

290' TO 296' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

296' TO 329' - BROWN & WHITE SANDY CLAY WITH STRIPS OF WHITE ROCK

329' TO 337' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN & YELLOW CLAY - 30%

337' TO 350' - SHALE