*					<u> para tina tina tina tina tina tina tina tin</u>	
ATER WELL RECORD Form WWC-5		/C-5	Division of Water Resources App. No.			
1 LOCATION OF WATER WELL: County: FINNEY	Fraction 1/4 SW 1/4 SE	1/4 NW 1/4	Section Number 12	Township No. T 23 S	Range Number R 34 □E 🗗 W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here		direction	Global Positioning System (GPS) information:			
NW CORNER OF HOLCOMB - 5 MILES NORTH,		iere [].	Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
2,825 FT. NORTH & 3,935 FT. WEST			Elevation:			
2 WATER WELL OWNER: REBECCA GRAHAM RR#, Street Address, Box #: 18250 CR 162			Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code : NATHROP, CO 81236			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL				3 m, 3-5 m,	5-15 m, ∐ >15 m	
SECTION BOX: Denth(s) Group	SECTION BOX: Depth(s) Groundwater Encountered (1) # (2) # (2)					
WELL'S STA	N WELL'S STATIC WATER LEVEL202					
L_NWNE EST. YIELDgpm. Well water was						
W Bore Hole Diameter 30						
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well						
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
S If yes, mo/day/yr sample was submitted						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter16						
Casing height above land surface12						
✓ Steel Stainless Steel PVC Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From						
From						
Grout Intervals: From						
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedward Feedward Feerfilizer storage Oil well/see well						
Direction from well SOUTHWEST FROM TO LITHOLO		Distance fro	om well275.FT\$	SOUTH-24.FT)	WEST	
TROM TO EITHOLO	dic Log	FROM 1	ro litho. Lo	G (cont.) <u>or</u> PLU	GGING INTERVALS	
SEE ATTACHED LO	3				Tradition of the second of th	
	The state of the s				and the second of the second o	
						
7 CONTRACTOR'S OR LANDOWNE	D'S CEDTIFICATION	This				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .4-25-13						
under the business name ofMINTER-WILSON DRILLING CO., INC., by (signature) 100 and						
(white, blue, pink) to Kansas Depar tment of Health and Environment Bureau of Water Geology Section 1000 SW Joshop St. Suite 420 Teacher St. Sui						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						

The Professionals MINTER-WILSON DRILLING CO. Unique Installation Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A GARDEN CITY, KANSAS 67846

NAME

GRAHAM FARMS

COUNTY

FINNEY

DATE

2-8-13

LOCATION:

NW 1/4 12-23-34 - HWY. 50 & LOWE ROAD - 3 MILES NORTH,

1 MILE WEST, 1-1/2 MILES NORTH &

1/4 MILE EAST

- 300 FT. NORTHEAST OF EXISTING WELL

STATIC WATER LEVEL -

TEST #1

2' - TOP SOIL 0' TO

8' - BROWN SANDY CLAY

8' TO 176' - BROWN CLAY

176' TO 208' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY

208' TO 230' - BROWN CLAY

230' TO 240' - FINE TO MEDIUM SAND & GRAVEL

240' TO 260' - BROWN CLAY

260' TO 275' - FINE TO MEDIUM SAND & GRAVEL - 10% CLAY - TIGHT

275' TO 310' - FINE TO MEDIUM SAND & GRAVEL - LOOSE

310' TO 315' - BROWN YELLOW CLAY

315' TO 320' - SHALE

TEVED

YEVALA DEC ENEVEY