WATER WELL RECORD	Form W	/WC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WEI		/ W C-3	Section Number   Township No.   Range Number
County: Finney	½ SE ¼ SV	N 1/4 SW 1/4	1 T 23 S R 34 DE WW
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here			Latitude: .38,076380 (in decimal degrees)
From Holcomb, 5 miles north, 3/4 mile west			Longitude: 101.006801 (in decimal degrees)
			Elevation: 2945
2 WATER WELL OWNER: Roger Unruh			Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:
RR#, Street Address, Box #: 625 cowgil dr.			GPS unit (Make/Model: I-phone
City, State, ZIP Code : garden city, ks. 67846			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
			Est. Accuracy:
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL			
SECTION ROX: Depth(c) Groundwater Encountered (1) ft (2) ft (3) ft			
N WELL'S STATIC WATER LEVEL. 214ft. below land surface measured on mo/day/yr10/4/14			
Pump test data: Well water wasft. after hours pumping gpm			
EST. YIELDgpm. Well water wasft. after hours pumping gpm			
w           E   Bore Hole Diameterin. tott., andn. tott.			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well			
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)  ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well			
Was a chemical/bacteriological sample submitted to Department?  Yes No			
S If yes, mo/day/yr sample was submitted			
mile  Water well disinfected? ✓ Yes ☐ No			
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter .16 in. to			
Casing height above land surface.	.12 in., Weigh	nt	lbs./ft., Wall thickness or gauge No
TYPE OF SCREEN OR PERFORATION MATERIAL:			
☑ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
GRAVEL PACK INTERVALS: From ft. to ft. to			ft. ft. ft.
From			
Grout Intervals: From			
What is the nearest source of possible			
	ateral lines 🔲 Pit privy	Livestock p	
	esspool		e Abandoned water well
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☑ Oil well/gas well  Direction from well .NW Distance from well .800'.			
	IOLOGIC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
TROW TO BITTI	IOLOGIC DOG	T KOW	Instal 2" vent/access on casing at
			4' below land surface grouted
			with neat cement grout from 0-4',
			bentonite grout observed below
			4', disinfected then capped
	•		vent/access.
		1 1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☑ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year) .10/4/14			
under the business name of Kansas Well-cam by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to			
Kansas Department of Health and	Environment, Bureau of Water, Ge	eology Section, 10	000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.

http://www.kdheks.gov/waterwell/index.html