LLOCATION OF WATER WELL: County:RENO		Fraction NE 1/4 NE 1/4 NE 1/4			Section Number 24		Township Number 23 SOUTH		Range Number 4 WEST			
Distance and direction from nearest town or city street address of well if located within city? EB 5 A - From intersection of US 50 and BurMac Rd 2 miles west and 1 mile nroth												
WATER WELL OWNER: Equus Beds Groundwater Management District RR#, St. Address, Box #: 313 Spruce Street Board of Agriculture, Division of Water Resources City, State, ZIP Code Halstead Kansas 67056-1925 Application Number: NA												
3 LOCATE WELL'S LO WITH AN "X" IN SECT	4 DEPTH OF COMPLETED WELL 55.0 feet ELEVATION: UNK feet Depth Groundwater Encountered 1 12.87 feet 2 feet 3 feet											
W1 m	WELL'S STATIC WATER LEVEL 12.87 feet below land surface measured on 11/29/00 mo/day/yr Pump test data: Well water was feet after hrs pumping gpm Estimated Yield 26.0 gpm: Well water was feet after hrs pumping gpm Bore Hole Diameter 6.0 inch to 58.0 feet and inch to feet WELL WATER IS USED AS: ☐ 5 Public water supply ☐ 8 Air conditioning ☐ 11 Injection ☐ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☑ 10 Monitoring well EB 5 A Was a chemical/bacteriological sample submitted to Department? NO ; If yes, when mm/dd/yy sample was submitted Water Well Disinfected? NO											
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped 2 PVC 4 ABS 7 Fiberglass 1 Threaded Blank casing diameter Steel 2.0 inches to 7.0 feet, Diameter PVC 2.0 inches to 45.0 feet, Diameter in to Casing height ABOVE land surface 34.8 inches, weight pounds/foot Wall thickness or gauge No TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement												
□ 1 Steel □ 3 Stainless steel □ 5 Fiberglass □ 8 RMP (SR) □ 11 Other (specify □ 2 Brass □ 4 Galvanized steel □ 6 Concrete tile □ 9 ABS □ 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: □ 5 Gauzed Wrapped □ 8 Saw Cut □ 11 None (open hole) □ 1 Continuous Slot □ 3 Mill Slot □ 6 Wire Wrapped □ 9 Drilled holes □ 2 Louvered shutter □ 4 Key Punched □ 7 Torch cut □ 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 55.0 feet to 45.0 feet, From feet to feet												
GRAVEL PACK INTERVALS: From 55.0 feet to 40.0 feet, From feet to feet From feet to feet to feet GRAVEL PACK INTERVALS: From 55.0 feet to 40.0 feet, From feet to feet												
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From(1) 40.0 feet to 3.0 feet, From (3) 3.0 feet to 0.0 feet, From feet to feet What is the nearest source of possible contamination: 1 Septic tank												
0.0 5.0	LOAM. cl	avev. bro)G		FROM	TO		LIT	HOLOGIC LO	<u>3</u>	
	CLAY, wi			wn				†				
	GRAVEL, brown											
	SAND, coarse, clay streaks CLAY, greenish tan											
								 				
	SAND, m SAND, m			o tan				<u> </u>				
	CLAY	odium, o	Jais	o, tarr	-			1				
		, –						 		<u> </u>		
								ļ				
								 				
	<u> </u>							-				
OWNER'S CERTIFICATION: This water well was constructed on 10/7/00(mo/day/year under my jurisdiction and this record is true to the best of my knowledge and belief. This Water Well Record was completed on 2/92/01(mo/day/year) under the business name of Equus Beds Groundwater Management District No. 2. Kansas Water Well License No. motionalicable.												
								(Signatur	e and Title)	-		