1 LOCATION OF WATER WELL: County:RENO	Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 24	Township Number 23 SOUTH	Range Number 4 WEST
Distance and direction from nearest town or city street address of well if located within city? EB 5 AA - From Intersection of US 50 and BurMac Rd 2 miles west and 1 mile nroth				
WATER WELL OWNER: Equus Beds Groundwater Management District RR#, St. Address, Box #: 313 Spruce Street Board of Agriculture, Division of Water Resources City, State, ZIP Code Halstead Kansas 67056-1925 Application Number: N/A				
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL 18.0 feet ELEVATION: UNK feet WITH AN "X" IN SECTION BOX: Depth Groundwater Encountered 1 10.46 feet 2 feet 3 feet				
W N N N N N N N N N N N N N N N N N N N	WELL'S STATIC WATER LEVEL 10.4 Pump test data: Well Estimated Yield 1.33 gpm: Well Bore Hole Diameter 6.0 inch to WELL WATER IS USED AS: 1 Domestic 3 Feedlot 2 Irrigation 4 Industrial Was a chemical/bacteriological sample mm/dd/yy sample was submit	water was water was fe 20.0 feet and 5 Public water 6 Oil field wate 7 Lawn and ga	eet after hrs pur inch to feet supply	umping gpm mping gpm t ditioning 11 Injection ering 12 Other (specify below) oring welL EB 5 AA
S TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Blank casing diameter Steel 2.0 inches to 7.0 feet, Diameter PVC 2.0 inches to 8.0 feet, Diameter in to Casing height ABOVE land surface 34.8 inches, weight pounds/foot Wall thickness or gauge No				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed Wrapped 8 Saw Cut 11 None (open hole) 1 Continuous Slot 3 Mill Slot 6 Wire Wrapped 9 Drilled holes 2 Louvered shutter 4 Key Punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 18.0 feet to 8.0 feet, From feet to feet From feet to feet to feet				
GRAVEL PACK INTERVALS: From 18.0 feet to 8.0 feet, From feet to feet From feet to feet to feet From feet to feet to feet				
GROUT MATERIAL: 1 Neat cement				
0.0 5.0 CLAY. I	oamy, brown	FROM TO	<u>LIII</u>	HOLOGIC LOG
5.0 9.0 CLAY, v	vith sand, coarse			
	coarse, with gravel			
17.0 18.0 SAND, 0 18.0 20.0 CLAY, s	coarse, clay streaks	· · · · · · · · · · · · · · · · · · ·		
2010 2211,1	, and a			
			-	
		<u> </u>		
OWNER'S CERTIFICATION: This water well was constructed on 10/10/00(mo/day/year under my jurisdiction and this record is true to the best of my knowledge and belief. This Water Well Record was completed on 2/12/01(mo/day/year) under the business name of Equus				
Beds Groundwater Management District No. 2. Kansas Water Well License No. not applicable.				

(Signature and Title)