| WATE | | RECORD | Form WWC | -5 | Division o | of Water | Resources; App. No. | 45,400 | |
|---|--|---|--|--|--|--|--|--|--|
| | ATION O | F WATER WELL: | Fraction NE 1/4 SW 1/4 | SW 1/4 | Section Nu | I | Township Number T 23 S | Range Number R 4 E W | |
| Dista withi | nce and dire | ction from nearest town or city so proximately 5 3/4 miles eas | eet address of well if located | | Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 38.059868 Longitude: -97.77088 | | | | |
| 2 WATER WELL OWNER: Integra Commercial Realty, LLC RR#, St. Address, Box # City, State, ZIP Code : c/o Lane Neville 8846 East Diamond Rim Drive Scottsdale, Arizona 85255 | | | | | | Elevation: unknown Datum: NAD 83 Data Collection Method: WAAS GPS Unit | | | |
| LOC WIT SEC | | Depth(s) Groundwater WELL'S STATIC W. Pump test dar Est. Yield unknown gpr WELL WATER TO 1 Domestic 3 2 Irrigation 4 | ta: Well water was m: Well water was BE USED AS: 5 Pu Feedlot 6 Oil fid Industrial 7 Dome | 8 ft ot checke blic water seld water sestic (lawn mitted to | ft. (in the second of the seco | 2) I surface 8 Air co 9 Dewa 10 Moni | hours pumping | gpm gpm gpm gpm gpm gpection well ther (Specify below) | |
| Blank ca Casing h TYPE C 1 2 SCREE | Steel : PVC : asing diam neight abov PF SCREE Steel : Brass N OR PER Continuou | SING USED: 5 Wrough RMP (SR) 6 Asbesto ABS 7 Fibergla in to 29 (steel and surface 24 NOR PERFORATION MATE 3 Stainless Steel 5 Fibergla Galvanized Steel 6 Conformation OPENINGS ARIS slot 3 Mill slot 5 shutter 4 Key punched 6 | in., weight 49.56 stee ERIAL: erglass 7 PVC ncrete tile 8 RM (SE: Gauzed wrapped 7 | 12 i 12 i 10/10.31 PVC 9 SR) 10 | n. to 39 (P\ lbs./ft. Wal ABS Asbestos-C | Bolt /C) ft., If thickr ement led holes | Welded Threaded Diameter ness or gauge No. 11 Other (Specify) 12 None used (open hole | in. to ft. 375 steel/.420 PVC | |
| SCREE | N-PERFO | RATED INTERVALS: From From PACK INTERVALS: From From | 39 ft. to | 102 | 2 ft., F | rom | ft. to ft. to | ft. | |
| | GRAVEL | PACK INTERVALS: From From | 33 ft. to ft. to | 104 | 4 ft., F ft., F | rom rom | ft. to | ft. ft. | |
| Grout I. What is 1 Septi 2 Sewe | UT MATE Comp ntervals: the nearest so the tank the lines | RIAL: 1 Neat Cement 2 acted Soil From 0 ft. to ource of possible contamination: 4 Lateral lines 7 5 Cess pool 8 | Cement grout 3 Ber 5 ft., From Pit privy 1 Sewage lagoon 1 | 5 0 Livestoo 1 Fuel sto | ft. to2 ck pens | 7 ft 13 Insec 14 Aban | Bentonite Holep | lug | |
| Direction | | ? | I | low man | U | 15 On w | | | |
| FROM 0 | TO 4 | LITHOLOGIC LO Topsoil, sandy |)G | FROM | TO | | PLUGGING INTE | RVALS | |
| 4 | 8 | Clay, brown, sandy | | | | | | | |
| 8 | 15 | Sand, very fine | | | | _ | | | |
| 15 40 | 40 63 | Clay, brown, sandy, some Sand, very fine | e sand streaks | | | | | | |
| 63 | 70 | Clay, gray and tan, sandy | 1 | | | | | | |
| 70 | 92 | Sand, very fine | | | | | | | |
| 92 | 104 | Clay, brown, sandy | | | | | | | |
| | | | | | - | | | | |
| | | | | | | | | 4444 | |
| under my Kansas V | y jurisdiction Water Well (| and was completed on (mo/day/Contractor's License No. 1 ame of Clarke Well & Equip | (year) 9-26-06 85 This Water | and Well Reco | d this record i | is true to leted on | the best of my knowled mo/day/year) 10 | ge and belief. | |
| INSTRUC copies to k | TIONS: Use Kansas Depar | typewriter or ball point pen. <u>PLEASE</u> ment of Health and Environment, Bu e to WATER WELL OWNER and re | PRESS FIRMLY and PRINT of reau of Water, Geology Sec | learly. Pleation, 1000 | ase fill in blank SW Jackson St | s, underli | ne or circle the correct ans 20, Topeka, Kansas 66612- | | |