262 WATER	9133 R WELL	RECORD	Form WWC-	5	Division	of Water	Resources; App. No.	45,398	
1 LOCATION OF WATER WELL:			Fraction			umber	Township Number		
	y: Reno		SW 1/4 NE 1/4		9 Clabal Bar		T 23 S	R 4 E W	
		ction from nearest town or city st proximately 6 miles east of			Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: 38.06145				
***************************************	ordy.	,		Longitude: -97.761062					
2 WATER WELL OWNER: Integra Commercial Realty, LLC					Elevation: Unknown				
	St. Addre		d Rim Drive		Datum:				
City,	State, ZIP	Code : Scottsdale, AZ 8]	Data Collection Method: WAAS GPS Unit				
3 LOCA	TE WEI	L'S 4 DEPTH OF COMP	LETED WELL	126	6	ft.			
	ATION						ft (3)	ft,	
	I AN ''X''	IN WELL'S STATIC WA	TERLEVEL 6	Encountered (1) ft. (2) ft. (3) ft, TER LEVEL 6 ft. below land surface measured on mo/day/yr 12-12-08					
SECT	TION BOX	Pump test dat	a: Well water was No	t checked	ft. after	u surrace	hours pumping	y/ylgpm	
	- 1 - 1 -	Est. Yield Unknown gpr	n: Well water was		ft. after_		hours pumping_	gpm	
NW	/	WELL WATER TO I	BE USED AS:(5) Pul	olic water s	supply	8 Air c	onditioning 11 I	njection well	
w L		_	Feedlot 6 Oil fie	eld water su	pply	9 Dewa	atering 12 (Other (Specify below)	
		2 Irrigation 4	Industrial 7 Dome				-	(·F···)	
SW	SE ^x	Was a chemical/bacte		-				If ves mo/day/yrs	
						_		11 y 00, 1110/ day/ y 15	
	S	Sample was submitted						· 	
			t Iron 8 Con						
\sim		RMP (SR) 6 Asbesto		er (specify	y below)		Welded_	,	
		ABS 7 Fibergla		355				1	
Blank casing diameter 12 in. to (Steel) 0-29 ft., Diameter 12 in. to (PVC) 29-39 ft., Diameter in. to ft.									
Casing height above land surface 24 in., weight 49.55 lbs./ft. Wall thickness or gauge No. 0.375 TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)									
2	Brass	4 Galvanized Steel 6 Cor		SR) 10	Asbestos-	Cement	12 None used (open h	nole)	
SCREEN	OR PER	FORATION OPENINGS ARE	S:	.					
		s slot (3) Mill slot 5						le)	
		Shutter 4 Key punched 6						DVC 70 00 A	
SCREEN	N-PERFOR	RATED INTERVALS: From	SS 99-111 ft. to	DVC 111	1 124 ft	From	55 /5-/9 II. to	PVC 79-99 ft.	
(GRAVEI	PACK INTERVALS: From	30 ft to	124	1-124 10., ft	From		ft.	
·	ord i v EE	From	ft. to	 -	ft.,	From	ft. to	ft. ft.	
6 GROU	T MATE	RIAL: 1 Neat Cement 2	Cement grout 3 Ber	ntonite 4	Other	-			
		_				30 .	. p		
Grout In What is the		From 5 ft. to ource of possible contamination:	ŕ				t., From		
1			1 2	0 Livestoc	•		cticide Storage	(16) Other (specify	
2 Sewer		~ .				ndoned water well	below) None known		
	rtight sewer		i coayai a	2 Fertilize	-	15 Oil V	well/gas well _		
Direction FROM	from well	LITHOLOGIC LO		How many FROM	TO		PLUGGING INT	EDWAIG	
0	2	Topsoil		79	87	Clay (gray and brown, sa		
2	10	Sand, very fine to fine, loc	ose	87	93		very fine to fine, lo		
10	14	Clay, brown, white, sandy		93	99		prown and gray, sa		
14	26	Sand, very fine to fine, loc	ose	99	111		very fine to fine, lo		
26	37	Clay, light gray, sandy, so	2000-	111	124	Clay, l	prown and gray, sa	ndy, hard	
37	45	Sand, very fine to fine, loc							
45	49	Sand, very fine to fine, clay streaks, loose							
49	72	Clay, gray, sandy, soft, w							
72 74	74 77	Sand, very fine to fine, loc Clay, gray, sandy, soft)SE			***			
77 79 Sand, very fine to fine, loose						-			
		'S OR LANDOWNER'S CE		his water w	vell was (1)	Conetr	nicted (2) reconstru	octed (3) plugged	
under my	jurisdiction	and was completed on (mo/day)	year) 12-12-08	B and	this record	l is true to	the best of my knowle	edge and belief.	
•	-							2-22-08	
		ame of Clarke Well & Equip			ignature)	18	- Pin		
		typewriter or ball point pen. <u>PLEASE</u> ment of Health and Environment, Bu							
		e to WATER WELL OWNER and re						2-1307. Telephone	