265 WATEF			CORD	Form WWC	-5	Division	of Water	Resources; App. No.	45,398	
			TER WELL:	Fraction SW 1/4 NE 1/4	SE 1/4	Section N				
	ty: Reno		om nearest town or city str			Global Po		T 23 S		
			ately 6 miles east of h		cated	Global Positioning Systems (decimal degrees, min. of 4 digits)  Latitude: 38.060946  Longitude: -97.760249				
			Table and							
			NER: Integra Commercia  # c\o Lane Neville	al Realty, LLC		Elevation				
	St. Addre State, ZIF		`″ ∴ 8846 East Diamon				Datum: NAD83			
			Scottsdale, AZ 60					Method: WAAS GP	S Unit	
	TE WEI	LL'S	4 DEPTH OF COMPI							
	ATION I AN ''X''	ın l	Depth(s) Groundwater WELL'S STATIC WA	Encountered (1)		ft.	(2)	ft. (3)	ft,	
	TION BO		WELL'S STATIC WA	TER LEVEL1	2f	t. below lan	d surfac	e measured on mo/day	<sub>y/yr</sub> 12-17-08	
	N		Pump test data	a: Well water was - N	ot check	ed ft. after_		hours pumping_	gpm	
			Est. Yield Unknown gpm							
NW	/NE-	1 1	WELL WATER TO B	•						
w	+	E						ratering 12 (	Other (Specify below)	
sw	SE <u>x</u> -		2 Irrigation 4			-		,		
l	Ī		Was a chemical/bacter	iological sample sub	mitted to	Departmen	nt? Yes	No _ <b>√</b> _ :	If yes, mo/day/yrs	
<u> </u>	S	┛ ╽	Sample was submitted		Wate	r well disint	fected?	Yes 🗸 No		
5 TVP		SING I						JOINTS: Glued	Clamped	
$\sim$			P (SR) 6 Asbestos	-Cement 9 Ot	her (spec	ify below)		Welded	<b>V</b>	
~			7 Fiberglas		` *	•		Threaded	I	
Blank casing diameter 12 in. to (Steel) 0-32 ft., Diameter 12 in. to (PVC) 32-41 ft., Diameter in. to ft.										
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.										
TYPE O	F SCREEI Steel	N OR P	PERFORATION MATE inless Steel 5 Fibe	RIAL: rglass 7 PVC		ABS		11 Other (Specify)		
1	Brass		vanized Steel 6 Con	_						
_			TIQN OPENINGS ARE		(510)	0 115005005	Comon	12 Trone asea (open i	ioic)	
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)										
			4 Key punched 6							
SCREEN	N-PERFO	RATEL	O INTERVALS: From							
	CD 4 1 1 1 1 1 1	D. CI	From	SS 88-97 ft. to	PVC 9	7-127 ft.,	From	SS 127-134 ft. to		
	GRAVEL	PACK	INTERVALS: From From	ft. to	1	08 II.,	From -		ft. ft.	
6 CROI	TT MATE	CRIAL	: 1 Neat Cement 2				-			
			-				20			
Grout Ir	ntervals: he nearest s	Fro source o	om 5 ft. to	25 ft., From		ft. to	30 f	t., From	ft. to ft.	
1 Septi			4 Lateral lines 7 l		10 Livesto	ock pens		ecticide Storage	(16) Other (specify	
2 Sewe	r lines		· .	0 0	11 Fuel st	U		indoned water well	below) None known	
	rtight sewer		6 Seepage pit 9 ]	coajara		er Storage	15 Oil	well/gas well	INOUG KHOWII	
Direction FROM	n from wel TO	<u>1?</u>	LITHOLOGIC LO		How mai			PLUGGING INTE	EDMALC	
0	2	Tops	. 74	<u> </u>	123		Sand	very fine to fine	CRVALS	
2	16		d, very fine to fine	7.0	13			gray, with streaks o	f sand	
16	19		, gray, sandy				,	9,		
19	32	Sand	d, very fine to fine							
32	44		, gray, sandy	50 m						
44	75		d, very fine to fine							
75 77	77 85		, gray, sandy d, very fine to fine	· · · · · · · · · · · · · · · · · · ·						
85	90		, gray, sandy							
90	99		d, very fine to fine	3.776	-					
99	123		, gray, sandy	,						
7 CONT	RACTOR	R'S OR	LANDOWNER'S CE	RTIFICATION:	This water	well was (1)	const	ructed (2) reconstru	icted (3) plugged	
under my	jurisdiction	n and wa	as completed on (mo/day/	year)12-17-0	10 a	nd this record	is true to	the best of my knowle	dge and belief.	
							pleted on		2-22-08	
			Clarke Well & Equipr ter or ball point pen. PLEASE			(signature)	nka urd	Classes	See A see A	
copies to K	Cansas Depar	tment of	Health and Environment, Bur	eau of Water, Geology S	ection, 1000	) SW Jackson	St., Suite 4	120, Topeka, Kansas 66612	swers. Send top three 2-1367. Telephone	
785-296-5	522. Send or	ne to WA	TER WELL OWNER and re	tain one for your records.	Fee of \$5.	00 for each cor	nstructed v	vell.		