| 266<br>WATER   | 9133<br>R WELI   |         | Well #1<br>C <b>ORD</b>   | Form WWC-   | .5          | Division                      | of Water                              | Resources; App. No.                                   | 45,398                 |  |
|--|--|---------|---|---|-------------|-------------------------------|---------------------------------------|---|------------------------|--|
|  |  |         | TER WELL:   | Fraction  | CF 1/4      | Section N                     |                                       |   |                        |  |
| County: Reno SE 1/4 NW 1/4 SE 1/4  Distance and direction from nearest town or city street address of well if located  |  |         |   |   |             |                               |                                       | T 23 S  | R 4 E (W               |  |
|  |  |         | rom nearest town or city s<br>nately 6 miles east of              | Global Positioning Systems (decimal degrees, min. of 4 digits)  Latitude: 38.061694 |             |                               |                                       |   |                        |  |
| ,  |  |         |   |   |             |                               | Longitude: -97.761901                 |   |                        |  |
| 2 WATER WELL OWNER: Integra Commercial Realty, LLC.  |  |         |   |   |             | Elevation: Unknown            |                                       |   |                        |  |
| RR#, St. Address, Box # : c/o Lane Neville 8846 Diamond Rim Drive  |  |         |   |   |             | Datum: NAD83                  |                                       |   |                        |  |
| City, State, ZIP Code : 8846 Diamond Rim Drive : Scottsdale, AZ 85255  |  |         |   |   |             |                               | Data Collection Method: WAAS GPS Unit |   |                        |  |
| 3 LOCA   | TE WEI   | LL'S    | 4 DEPTH OF COM  | PLETED WELL   | 12          | 25                            | ft.                                   |   |                        |  |
|  | ATION  | I TAT   |   |   |             |                               |                                       | ft. (3)   | ft.                    |  |
| 1  | WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 6.30 ft. below land surface measured on mo/day/yr 12-30-08 |         |   |   |             |                               |                                       |   |                        |  |
| N Pump test data: Well water was Not checked ft. after hours pumping gn  |  |         |   |   |             |                               |                                       |   |                        |  |
| Est. Yield Unknown gpm: Well water wasft. after hours pumping WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection we   |  |         |   |   |             |                               |                                       |   | gpm                    |  |
| NW   | /NE-   | -       | WELL WATER TO   | BE USED AS: (5) Pul   | blic water  | supply                        | 8 Air                                 | conditioning 11                                       | Injection well         |  |
| W E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify bel   |  |         |   |   |             |                               |                                       |   | Other (Specify below)  |  |
|  |  |         |   |   |             |                               |                                       |   |                        |  |
| SW  SE   |  |         |   |   |             |                               |                                       |   |                        |  |
| Sample was submitted Water well disinfected? Yes V No  |  |         |   |   |             |                               |                                       |   |                        |  |
| 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped   |  |         |   |   |             |                               |                                       |   |                        |  |
|  | STYPE OF CASING USED: 5 wrought not 8 concrete the CASING JOINTS. Glided V Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded V                  |         |   |   |             |                               |                                       |   |                        |  |
| 2 PVC 4 ABS 7 Fiberglass Threaded  |  |         |   |   |             |                               |                                       |   |                        |  |
| Blank casing diameter 12 in. to Steel 0-36 ft., Diameter 12 in. to PVC 36-46 ft., Diameter in. to ft.  |  |         |   |   |             |                               |                                       |   |                        |  |
| Casing height above land surface 24 in., weight 49.55 lbs./ft. Wall thickness or gauge No375   |  |         |   |   |             |                               |                                       |   |                        |  |
| TYPE OF SCREEN OR PERFORATION MATERIAL:  |  |         |   |   |             |                               |                                       |   |                        |  |
| 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)   |  |         |   |   |             |                               |                                       |   |                        |  |
| 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:   |  |         |   |   |             |                               |                                       |   |                        |  |
| 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)   |  |         |   |   |             |                               |                                       |   |                        |  |
| 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify)   |  |         |   |   |             |                               |                                       |   |                        |  |
| SCREEN-PERFORATED INTERVALS: From SS 46-52 ft. to PVC 52-92 ft., From SS 92-110 ft. to PVC 110-123 ft.   |  |         |   |   |             |                               |                                       |   |                        |  |
|  | From ft. to ft., From ft. to ft.   |         |   |   |             |                               |                                       |   |                        |  |
| 1  | GRAVEL PACK INTERVALS: From 32 II. 10 123 II., From II. 10 II.   |         |   |   |             |                               |                                       |   |                        |  |
| 6 CDOI   | TATATE   | DIAI    | From  |   |             |                               | From _                                | II. to  | ft.                    |  |
|  |  |         | _   | Cement grout 3Ber   |             | _                             | <b>-</b>                              | <b></b>   |                        |  |
| Grout In   | itervals:  | Fr      | om 5 ft. to of possible contamination                             | 25 ft., From  | 25          | ft. to                        | 32 f                                  | ct., From   | ft. to ft.             |  |
| 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insectic  |  |         |   |   |             |                               |                                       | ecticide Storage                                      | (16) Other (specify    |  |
| 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel stor   |  |         |   |   |             |                               | Nana lasaran                          |   |                        |  |
| 1  | rtight sewer   |         |   | 1 coujuiu   |             | er Storage                    | 15 Oil                                | well/gas well   | None known             |  |
|  | from wel   | 1?      |   |   | low man     | <del></del>                   | <del></del>                           | PL LIGORIO DIE  |                        |  |
| FROM 0   | TO 3   | Tops    | LITHOLOGIC L  | .00   | FROM        | TO                            | Cond                                  | PLUGGING INT  | ERVALS                 |  |
| 3  | 11   |         | y, brown, sandy, soft   |   | 58          |                               |                                       | very fine, loose white, brown, sand                   | ty soft                |  |
| 11   | 12   |         | d, very fine, loose   |   | 68          |                               |                                       | very fine, loose                                      | iy, soit               |  |
| 12   | 14   |         | y, brown, sandy, soft   |   | 71          |                               |                                       | white, brown, sand                                    | ly, soft               |  |
| 14   | 20   | San     | d, very fine, loose   | 7   | 87          | 95                            |                                       | very fine, loose                                      |                        |  |
| 20   | 23   | _       | ay, brown, sandy, soft 95 112 Clay, white, brown, sandy, soft     |   | ly, soft    |                               |                                       |   |                        |  |
| 23   | 39   |         | Sand, very fine, loose  |   | 112         |                               | Sand, very fine, loose                |   |                        |  |
| 39<br>40   | 40<br>47   |         | y, brown, sandy, soft   |   | 115         | 123                           | Clay,                                 | white, brown, sand                                    | ly, soft               |  |
| 47   | 52   | _       | y, white, sandy, soft<br>d, very fine, loose                      |   |             |                               |                                       |   |                        |  |
|  | 52 58 Clay, white and brown, sandy, soft   |         |   |   |             |                               |                                       |   |                        |  |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged   |  |         |   |   |             |                               |                                       |   |                        |  |
| under my jurisdiction and was completed on (mo/day/year)  12-30-08  and this record is true to the best of my knowledge and belief.  |  |         |   |   |             |                               |                                       |   |                        |  |
| Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 01-05-09  |  |         |   |   |             |                               |                                       |   |                        |  |
|  |  |         | Clarke Well & Equip   |   |             | signature)                    | 13                                    | s Chr   |                        |  |
| copies to K  | ansas Depart   | typewri | ner or ban point pen. <u>PLEAS</u><br>f Health and Environment. B | E PRESS FIRMLY and PRINT course of Water, Geology Sec                               | nearly. Ple | ase till in bla<br>SW Jackson | nks, under<br>St., Suite 4            | line or circle the correct a 420, Topeka. Kansas 6661 | nswers. Send top three |  |
| copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. |  |         |   |   |             |                               |                                       |   |                        |  |