

CORRECTION(S) TO WATER WELL RECORD (WWC-5)  
(to rectify lacking or incorrect information)

County: HAMILTON

Location listed as:

Section-Township-Range: 30-23s-40w

Fraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$ ): NW SW SW

Location changed to:

29-23s-40w

NW SW SW

Other changes: Initial statements: SEC. 30

Changed to: SEC. 29

Comments: WATER WELL RECORD INITIALLY FILED IN WRONG SECTION

verification method: OWNER OF WATER WELL CALLED TO GET CORRECT SECTION  
NOTED ON WATER WELL RECORD.

initials: RR date: 11-27-2007

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number  
 COUNTY: HAMILTON NW 1/4 SW 1/4 SW 1/4 30 T 23 S R 40 W

Distance and direction from nearest town or city street address of well if located within city?  
 SYRACUSE - EAST ON HIGHWAY 50-N 3 1/2, W3/4 & S 1/4 MILE

2 WATER WELL OWNER: BATTIN, ERNIE  
 RR#, St. Address, Box #: 2262 N. ROAD 8 Board of Agriculture, Division of Water Resources  
 City, State, ZIP code: ULYSSES, KS 67880- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 365 ELEVATION: 0  
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.  
 WELL'S STATIC WATER LEVEL 263 ft. below land surface measured on mo/day/yr 05/07/07  
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Estimated Yield 20 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Bore Hole Diameter 9 in. to 365 ft., and in. to 0 ft.  
 WELL WATER TO BE USED AS: DOMESTIC  
 Was a chemical/bacteriological sample submitted to department? No ;  
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CERTA-LOC  
 Blank casing diameter 5 in. to 365 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21 17  
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 300 ft. to 360 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 GRAVEL PACK INTERVALS: From 25 ft. to 365 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE  
 Grout Intervals: From 0 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 What is the nearest source of possible contamination: NONE  
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 10 FINE-MEDSAND 07 BLUE SHALE			
20	240	07 BLUE SHALE 24 THINROCLAYER			
240	280	07 BLUE SHALE 29 SANDSTONE 19 LAYERS			
280	380	29 SANDSTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 05/08/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 06/05/07 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Jessie Critch*