·			WATER WE	ELL RECORD	Form WV	VC-5	KSA 82a	-1212		MW-1
1 LOCATI	PALAE WA	CER WELL:	Fraction 1/4	NEG 1		Section	Number	Township	Number	Range Number
County:	and direction	from nearest town	or city street addres	s of well if locat	1/4	ity?	23	Т	23 _S	R 43 EW
		est Hwy 50,	Coolidge, K	S 		<u> </u>		. <u></u>	·	
2 WATE	R WELL OW	^{(NER:} Coolidge (General Store	eof. o\n e	Ochos					
		X # DOOLLAGE	104, Coolidge	e c/0 00e	OCHOR			Board o	f Agriculture, [Division of Water Resources
	e, ZIP Code	-							tion Number:	
3 LOCAT	E WELL'S L	OCATION WITH 4	DEPTH OF COMP	LETED WELL	33.0	Q f	. ELEVA	TION:		
AN "X"	IN SECTION	N BOX:	epth(s) Groundwater	Encountered	125	5.1	ft. 2		ft. 3	
ī ſ	1									12/12/96
T	<u>اين</u>	1								mping gpm
-		NE	st Yield	onm: Well wa	iter was		- ft at	fter	bours pur	mping gpm
	Est. Yield									
Wile W	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									i
-	ii		1 Domestic	3 Feedlot					•	Other (Specify below)
-	SW	SE	2 Irrigation	4 Industrial						
	!	! ,,	-							
<u> </u>				riologicai sample	e submitted	to Depar			-	mo/day/yr sample was sub-
-l -n/n= /			nitted					ter Well Disinfe	****	No X
-		CASING USED:		Vrought iron		oncrete t				d C lamped
1 St		3 RMP (SR)		sbestos-Cemen	t 9 Ot	ther (spe	cify below	v)	Welde	ed
(2)		4 ABS		iberglass						aded 🗶
										in. to ft.
Casing he	ight above la	and surface	🗘 in., v	weight <u>S</u>	CH 40 I	PVC ···	Ibs./1	ft. Wall thicknes	ss or gauge No	0
TYPE OF	SCREEN O	R PERFORATION I	MATERIAL:		C	PVC		10 A	Asbestos-ceme	nt
1 St	eel	3 Stainless s	teel 5 F	iberglass	8	RMP (S	SR)	11 (Other (specify)	
2 Br	ass	4 Galvanized	l steel 6 C	oncrete tile	9	ABS		12 N	None used (op-	en hole)
SCREEN	OR PERFOR	RATION OPENINGS	S ARE:	5 Gau	ized wrappe	ed .		8 Saw cut		11 None (open hole)
1 Co	ontinuous slo	t 3 Mill:	slot	6 Wire	wrapped			9 Drilled hole	es	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-	PERFORATI	ED INTERVALS:	From 33 . 0	ft. to .	1.8. e	٥	ft., Fror	n	ft. to	oft.
			From	ft. to .		المستعدد المستعدد	.ft., Fror	n	ft. to	o
(GRAVEL PA	CK INTERVALS:	From 33	ft. to			ft Fror	n	ft. to	o
			From	ft. to			· -		ft. to	
6 GROU	T MATERIAL	1 Neat cer	ment 2 ce	ment grout	<u> </u>	entonite			~~~~	
Grout Inte			to1.5	ft (ZE)om	' 5'	ft to	Surl	2002 ft From		ft. to
What is th		ource of possible co		,				tock pens		bandoned water well
_	eptic tank	4 Lateral		7 Pit privy				•		il well/Gas well
2 Sewer lines 5 Cess pool				· ·			11 Fuel storage		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit				8 Sewage lagoon 9 Feedyard			12 Fertilizer storage 13 Insecticide storage			mer (specify below)
ŀ	from well?	er intes o Seepag	e pit	9 reedyald				•	Contan	minated Site
FROM	TO		LITHOLOGIC LOG		FROM	<u>vi l</u>	How mar	ny reet?	PLUGGING IN	
			ETTTOLOGIO LOG		11101	*	<u>'</u>		· Localita ii	TICHYALO
	1						-			
GL	1.00	Surface si	lts and clay			-+-				
	23.50	Clayey Sil				-				
	33.00	Sand (SP)	C (FMD)		+-					
33.00	TD		-ahala							
33.00	עד ו	End of bor	enore							
										<u></u>
							1	Flush Mou	nt	
							i	waiver	_	
			•							
						1	1	D.Taylor		
								_	06	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was										
completed on (mo/day/year)/2/7/2										
			585	Inis Water	well Record		•		1 13/2	10/16
	business na						by (signat		Win K L	Sllle-
INSTRU	ICTIONS: Use ty th and Environm	pewriter or ball point pen ent. Bureau of Water Toi	peka, Kansas 66620-0001.	and <u>PRINT</u> clearly. F	Please fill in bla i-5545. Send or	inks, underl	ine or circle	the correct answers	s. Send top three o	copies to Kansas Department