			+	ELL RECORD F	orm WWC		32a-1212			
1 LOCAT	HANGE YA	TER WELL:	Fraction 1/4	NW 1/4 NW	1/4 S	Section Numb	er Townsh	nip Number 23 S		Number
	and direction	from nearest town cest Hwy 50,	or city street addre	ess of well if located		?	<u> </u>			
2 WATE	R WELL OV	VNER Coolidge Ge	meral Stor	a a/a Jac Ori			<u> </u>			
RR#, St.	Address, Bo	* P.O. Box 10	94. Coolida	e C/O JOE OC e. KS 67836	DOS	Board of Agriculture, Division of Water Resources				
					22 ()			cation Number:		-
AN "X	IN SECTION	OCATION WITH 4 N BOX:	DEPTH OF COM	PLETED WELL	بنايرور	ft. ELE'	VATION:	,		
÷ [1	N De		TER LEVEL						•tt. 96
	Xi		Pump tes	st data: Well water	was	. Delow land	after	hours o	umping	apm
Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after									umping	: gpm
1.							t., and	777ir	n. to 	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air condition							•	Injection we		
lī l	SW	SE	1 Domestic				9 Dewaterin	•		
2 Irrigation 4 Industrial 7 Lawn and garde Was a chemical/bacteriological sample submitted to Depart										
<u>₹</u>			as a cnemicai/bact tted	eriological sample su	bmitted to		' YesNo Water Well Disir		s, mo/day/yr s No	
5 TYPE	OF BLANK	CASING USED:		Wrought iron	8 Con	crete tile		3 JOINTS: Glue		
1 S		3 RMP (SR)		Asbestos-Cement						
(2)	VC	4 ABS								
Blank cas	sing diamete	r . 2 in.	to 33.0.						. in. to	ft.
Casing h	eight above	and surface	🤈 in.,	weight SCH			s./ft. Wall thickr	ness or gauge N	No	<u></u>
1		R PERFORATION N		,	المل		10	Asbestos-cem	ent	
l	teel	3 Stainless st		Fiberglass		8 RMP (SR) 11 Other (specify)				
2 Brass 4 Galvanized steel 6 Concrete tile						9 ABS 12 None used (open hole) pped 8 Saw cut 11 None (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed 1 Continuous slot 3 Mill slot 6 Wire wra							8 Saw cut 9 Drilled h		II NONE ((open noie)
	ouvered shu	_		7 Torch o	• •			pecify)		
		ED INTERVALS:	From 33.	ft. to	18	ft., F	rom	ft.	to	_
			From	ft. to	<u></u>	<u></u> ft., F	rom <u></u> .	<u></u> ft.	to	
<u> </u>	GRAVEL PA	ACK INTERVALS:	From 33	ft. to	<i>17</i>	ft., F	rom	ft.	to	<u>.</u> tt.
-1			From	ft. to	(^)	ft., F		ft.		ft.
Grout Inte	T MATERIA	1 Neat cerr		ement grout	(3) Ber	ntonite				
	()	ource of possible cor	• —	. 11., (20)	IL	•	estock pens		Abandoned w	
1 Septic tank 4 Lateral lines				7 Pit privy			el storage	F		
2 Sewer lines 5 Cess pool			ol	8 Sewage lagoo	n		rtilizer storage	16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit				9 Feedyard						
	from well?					How r	many feet?		minated a	Si
FROM	то		LITHOLOGIC LOC	à	FROM	то	-	PLUGGING	INTERVALS	
						-		· · · · · · · · · · · · · · · · · · ·		
GL	1.50	Surface sil	ts and clay	'S						
1.50 2	23.00	Clayey Silt								
23.00 3	33.00	Sand (SP)	· · · · · · · · · · · · · · · · · · ·							
33.00	TD	End of bore	hole							
							.			
					 				·	
	-	-			 		1			
	 				<u> </u>		Flush Mou	nt		
							waiver			
				D M 1						
						D. Taylor 10/24/96				
		OR LANDOWNER'S					econstructed, or	(3) plugged un		
complete	d on (mo/day	//year) <i>1.2/3</i> /	196			. and this re	ecord is true to t	he best of my k	nowledge and	
Water W	ell Contracto	r's License No5	85 · · · · · · · · · · · · · · · · · · ·	This Water We	II Record	was complete	ed on (mo/day/y	12/20	126	
under the	business na	ame of AFT				by (sig	nature)	Jaux f.	Sleen	
		ypewriter or ball point pen. ment, Bureau of Water, Top								as Department