

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>NE 1/4 SE 1/4 NW 1/4</u>	<u>2</u>	T <u>23</u> S	R <u>5</u> E <u>10</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/2 mi. E of Hutchinson</u>					
2 WATER WELL OWNER: <u>Ron Hansen</u>					
RR#, St. Address, Box # : <u>7100 N Madison</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Hutch, KS 67502</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>98</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>8-1-95</u>			
		Pump test data: Well water was <u>36</u> ft. after <u>2</u> hours pumping <u>25</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>102</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped	
3 RMP (SR)		6 Asbestos-Cement	9 Other (specify below)	Welded	
<u>2</u> PVC		7 Fiberglass		Threaded	
4 ABS					
Blank casing diameter <u>5</u> in. to <u>78</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>24</u> in., weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	<u>2</u> PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	<u>8</u> Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>78</u> ft. to <u>98</u> ft., From <u>60</u> ft. to <u>102</u> ft.					
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>35</u> ft., From ft. to ft.					
From <u>40</u> ft. to <u>55</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft., From <u>35</u> ft. to <u>40</u> ft., From <u>55</u> ft. to <u>60</u> ft.					
What is the nearest source of possible contamination:					
<u>1</u> Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? <u>N</u>		How many feet? <u>800</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>28</u>	<u>F Sand</u>			
<u>28</u>	<u>44</u>	<u>Sandy Br Clay</u>			
<u>44</u>	<u>50</u>	<u>F Sand</u>			
<u>50</u>	<u>75</u>	<u>V Sandy Br Gr Clay</u>			
<u>75</u>	<u>102</u>	<u>F Sand</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-1-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>8-12-95</u> under the business name of <u>Miller Drilling</u> by (signature) <u>E. Miller</u>					