


1 LOCATION OF WATER WELL: County: RENO		Fraction SW 1/4 SE 1/4 SE 1/4	Section Number 5	Township Number T 23 S	Range Number R 5 E
Distance and direction from nearest town or city street address of well if located within city? 204.97 FEET NORTH 1248.65 FEET WEST OF SOUTHEAST CORNER OF SECTION					
2 WATER WELL OWNER: REPUBLIC PAPERBOARD COMPANY RR#, St. Address, Box #: P.O. BOX 1267 City, State, ZIP Code: HUTCHINSON, KANSAS 67504-1267			VESTED RIGHT NO. RN-18 Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">  </div>		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 3 FEET ABOVE GROUND LEVEL Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr 12-12-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 616 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 38 in. to 57 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 18 in. to 40 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 36 in. weight lbs./ft. Wall thickness or gauge No. 0.375 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 37 ft. to 57 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 32 ft. to 57 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 0 ft. to 20 ft. From 20 ft. to 22 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? NONE					
FROM		TO		LITHOLOGIC LOG	
0		4		TOP SOIL	
4		11		GRAY SANDY CLAY	
11		31		BROWN MEDIUM TO COARSE SAND	
31		33		GRAY CLAY	
33		48		BROWN MEDIUM TO COARSE SAND/GRAVEL	
48		60		GRAY MEDIUM TO COARSE SAND/GRAVEL	
FROM		TO		PLUGGING INTERVALS	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1) constructed**, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **DECEMBER 12, 1995** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **581** This Water Well Record was completed on (mo/day/yr) **December 20, 1995** under the business name of **LAYNE, INC.** by (signature) *Jan W. Seley*