

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Reno</u>		<u>NE 1/4 SE 1/4 NW 1/4</u>		<u>2</u>		T <u>23</u> S		R <u>5</u> EW			
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/2 mi. E of Hutchinson - 2510 Linksland Dr</u>											
2 WATER WELL OWNER: <u>Scott Sellers</u> RR#, St. Address, Box # : <u>107 Road Runner Ln</u> City, State, ZIP Code : <u>Hutch, KS 67502</u>											
Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: <u>103</u> ft. ELEVATION:								
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL <u>23</u> ft. below land surface measured on mo/day/yr <u>5-13-96</u>								
			Pump test data: Well water was <u>34</u> ft. after <u>2</u> hours pumping <u>25</u> gpm								
			Est. Yield gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter <u>9</u> in. to <u>10.6</u> ft. and in. to ft.								
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
			2 Irrigation 4 Industrial <u>7</u> Lawn and garden only 10 Monitoring well								
			Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted								
			Water Well Disinfected? <u>Yes</u> No								
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped											
<u>OPVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded											
7 Fiberglass Threaded											
Blank casing diameter <u>5</u> in. to <u>8.3</u> ft. Dia in. to ft. Dia in. to ft.											
Casing height above land surface <u>12</u> in. weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>160</u>											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From <u>83</u> ft. to <u>103</u> ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>50</u> ft. From ft. to ft.											
From <u>50</u> ft. to <u>106</u> ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft. From <u>50</u> ft. to <u>55</u> ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage											
Direction from well? <u>E</u> How many feet? <u>100</u>											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
<u>0</u>		<u>22</u>		<u>F Sand</u>							
<u>22</u>		<u>63</u>		<u>Sandy Br + Gr Clay</u>							
<u>63</u>		<u>105</u>		<u>F Sand</u>							
<u>105</u>		<u>106</u>		<u>Sandy Br + Gr Clay</u>							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-13-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>5-25-96</u> under the business name of <u>Miller Drilling</u> by (signature) <u>[Signature]</u>											