


P18 2211057 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Keno Fraction: NE 1/4 SE 1/4 SE 1/4 Section Number: 7 Township Number: T 23 S Range Number: R 5 EW

Distance and direction from nearest town or city street address of well if located within city? 540 ft. W of Halstead & 15 ft. S. of 17th

2 WATER WELL OWNER: RR#, St. Address, Box #: City of Hutchinson Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Hutchinson KS 67504-1567 Application Number: 1528.1

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: 1528.1
Depth(s) Groundwater Encountered 1. 22 ft. 2. 27 ft. 3. 27 ft.
WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 27 ft. after 1 hours pumping 27 gpm
Est. Yield 27 gpm: Well water was 27 ft. after 1 hours pumping 27 gpm
Bore Hole Diameter 3.5 in. to 3 ft. and 1 in. to 27 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Barometer
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Flush
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Flush
Blank casing diameter 1 in. to 1 ft. Dia. 1 in. to 1 ft. Dia. 1 in. to 1 ft. Dia. 1 in. to 1 ft. Dia.
Casing height above land surface 37.2 in. weight 37.2 lbs./ft. Wall thickness or gauge No. Sch 40
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 12 None used (open hole)
SCREEN-PERFORATED INTERVALS: From 24 ft. to 27 ft. From 24 ft. to 27 ft. From 24 ft. to 27 ft. From 24 ft. to 27 ft.
GRAVEL PACK INTERVALS: From 24 ft. to 27 ft. From 24 ft. to 27 ft. From 24 ft. to 27 ft. From 24 ft. to 27 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 3 ft. From 0 ft. to 3 ft. From 0 ft. to 3 ft. From 0 ft. to 3 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-23-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-22-97 under the business name of BSI by (signature) Alison M. Swin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.