

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>NE 1/4 SW 1/4 NE 1/4</u>	<u>4</u>	T <u>23</u> S	R <u>5</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2507 N Meadowlake Dr in Hutchinson</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>9.5</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>2.7</u> ft. below land surface measured on mo/day/yr <u>6-8-97</u>			
		Pump test data: Well water was <u>5.0</u> ft. after <u>2</u> hours pumping <u>2.0</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>4.6</u> ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7</u> Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel 3 RMP (SR)		Welded			
<u>2</u> PVC 4 ABS		Threaded			
Blank casing diameter <u>6</u> in. to <u>3.4</u> ft. Dia <u>6</u> in. to <u>4.6</u> ft. Dia					
Casing height above land surface <u>12</u> in., weight		lbs./ft. Wall thickness or gauge No. <u>16.0</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7</u> PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped <u>8</u> Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>3.4</u> ft. to <u>4.1</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>2.2</u> ft. to <u>4.1</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other			
Grout Intervals: From <u>2</u> ft. to <u>2.2</u> ft., From <u>4.1</u> ft. to <u>4.6</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
<u>3</u> Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>E</u>		How many feet? <u>40</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	9	F Sand			
9	17	Sandy Br Clay			
17	26	Br & Gr Clay			
26	41	Sand & Gravel			
41	95	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-8-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>6-26-97</u> under the business name of <u>Miller Drilling</u> by (signature) <u>E. Miller</u>					