

241120

mw-20

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Leaw</u>	<u>SE 1/4 NE 1/4 SE 1/4</u>	<u>8</u>	<u>T 23 S</u>	<u>R 5 E</u>

Distance and direction from nearest town or city street address of well if located within city?

911 N. Halstead

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code :	

T & E Oil Co., Inc
911 N. Halstead
Hutchinson, KS 67501

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>68.5</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>17.5</u> ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL <u>16.77</u> ft. below land surface measured on mo/day/yr <u>5/28/97</u>
	Pump test data: Well water was . ft. after . hours pumping . gpm
	Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
Bore Hole Diameter . <u>8</u> in. to . ft. and . in. to . ft.	
WELL WATER TO BE USED AS:	
1 Domestic	5 Public water supply
2 Irrigation	6 Oil field water supply
3 Feedlot	7 Lawn and garden only
4 Industrial	8 Air conditioning
	9 Dewatering
	10 Monitoring well
	11 Injection well
	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes . No <u>X</u> . If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes . No <u>X</u>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter . <u>2</u> in. to <u>58.5</u> ft. Dia in. to . ft. Dia in. to . ft.			Threaded <u>Flush</u>
Casing height above land surface . <u>Flush</u> in. weight . <u>703</u> lbs./ft. Wall thickness or gauge No. <u>Sch 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From . <u>58.5</u> ft. to . <u>68.5</u> ft. From . . ft. to . . ft.			
GRAVEL PACK INTERVALS: From . <u>56.5</u> ft. to . <u>68.5</u> ft. From . . ft. to . . ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From . <u>0</u> ft. to . <u>1</u> ft. From . <u>1</u> ft. to . <u>56.5</u> ft. From . . ft. to . . ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well?		How many feet?	
FROM	TO	FROM	TO
<u>0</u>	<u>2</u>		
<u>2</u>	<u>11</u>		
<u>11</u>	<u>66.5</u>		
<u>66.5</u>	<u>67.5</u>		
<u>67.5</u>	<u>68.5</u>		
LITHOLOGIC LOG		PLUGGING INTERVALS	
<u>Clay</u>			
<u>Clay</u>			
<u>sand</u>			
<u>weathered shale</u>			
<u>Shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/28/97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>6/10/97</u> under the business name of <u>GSI</u> by (signature) <u>Allison M. Jovan</u>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.