LOCATION OF W	ATER WELL:	Fraction	R WELL RECORD	Form W	Section Numb	82a-1212 per Townshi	p Number	Range	Number
county: Renc		1 4 . 3	NW 1/4	$\nu\omega$ 14	17		3 s	R 5	EW)
stance and direction 1215	on from nearest towr East 4th	Ave., Hu	tchinson,	Ks.	city?	•			
WATER WELL)WNEH:	nis Dick							
R#, St. Address,	Box # : 121	5 E. 4th				Board	of Agriculture,	Division of Wa	ater Resource
ty, State, ZIP Coo		chinson,					ation Number:		
LOCATE WELL'S AN "X" IN SECT	N I	_ Depth(s) Ground	water Encountered	d 1 .!.?.		ft. 2	ft. :	3. ₃ <u>.</u>	ft.
• !		WELL'S STATIC	WATER LEVEL	17.86	ft. below land	surface measure	d on mo/day/yr	6-20-	7.7
\ <u>'</u>	_ NE	•	test data: Well				•		٠.
	1 , 1 18	Est. Yield	gpm: Well	water was .	f	t. after	hours po	mping	gpm
w	E	Bore Hole Diame	eter 8/2" .ir	1. to .C.S					
w - <u> </u>	! ' '	WELL WATER T	O BE USED AS:		water supply		ning 11	•	
_ sw _	_ SE	1 Domestic	3 Feedlot			9 Dewatering			
- 3;; -		2 Irrigation	4 Industrial	7 Lawn	and garden onl	y 10 Monitoring	well		
		Was a chemical/t	pacteriological san	nple submitted		? YesNo. Water Well Disinf		, mo/day/yr sa No	
TYPE OF BLAN	CASING USED:		5 Wrought iron	8 (Concrete tile	CASING	JOINTS: Glue	d Cla	mped
1 Steel	3 RMP (SR)	6 Asbestos-Cen	nent 9 (Other (specify be	elow)		led	
2 PVC	4 ABS	1-1	7 Fiberglass					adedX .	
lank casing diame	ter 2 , 37.5 i	in. to / S	ft., Dia						
asing height above	e land surface.F.W	SOM ME	in., weight			bs./ft. Wall thickno	ess or gauge N	loSCI	I 4.0
YPE OF SCREEN	OR PERFORATION	MATERIAL:		•	7 PVC		Asbestos-cem		
1 Steel	3 Stainless	steel	5 Fiberglass		8 RMP (SR)		Other (specify		
2 Brass	4 Galvanize		6 Concrete tile		9 ABS		None used (or		
CREEN OR PERF	ORATION OPENING			Sauzed wrapp		8 Saw cut		11 None (o	pen hole)
1 Continuous	slot 3 Mill	slot	6 \	Wire wrapped		9 Drilled ho			
2 Louvered sh	outter 4 Key	y punched	7 <i>~ '</i>	Forch cut		' '	ecify)		
CREEN-PERFOR	ATED INTERVALS:	From O				From			
		From	ر الماري الم	to	ft.,	From	ft.	to	
GRAVEL	PACK INTERVALS:	From •	5′ft.	to .13	ft.,	From	ft.	to	
		From	ft	to	ft.,	From	ft.	to	ft
GROUT MATER		ement _a / (2)Cement grout	್ನ, ಅ	Bentonite	From 4 Other ft., Fror			
	From 1.3' . (3)	t. to 🕽	ft., From .	ے ک					
	source of possible of		7.50	•		vestock pens		Abandoned wa	
1 Septic tank	4 Latera		7 Pit priv	•		uel storage		Dil well/Gas w	
2 Sewer lines			8 Sewage	•		ertilizer storage	16 (Other (specify	below)
	ewer lines 6 Seepa	ige pit	9 Feedya	ira		secticide storage many feet? 400	n'		
irection from well?	HOLLIN	LITHOLOGIC	LOG	FRO		many feet? 700	PLUGGING	INTERVALS	
0 4	Grass-Dk		ndy clay		10				
			, fine g						
		, earthy		Lulica					
1 6			trace of	Sand					
•			irm - sti						
7.5			o silt,					1000	
7.5 12		-	dry, no o	- 1					
		inded & s		uor ,					,
12 25			ne-veryc	nardo		F.M.OKO	MAK	ונו חדמא	M
23	4 ,		vel, wet			1 1 1 1 10 10	~~~.	or, racy c	
	at 17'.		WEL, WEL						
	at 1								
CONTRACTOR	S OR I ANDOMNED	'C SEDTIFICATI	ON: This water	oll was /1	netructed (a)	reconstructed or	(3) plugged up	der my juriedi	ction and we
CONTRACTOR	S OR LANDOWNER	75 IFICALI	ON: This water w	was (1) co					
	lay/year) . 6.7.9.	539	Th:- */-	tor Wall Dear	and this r	ecord is true to the ed on (mo/day/yr)		- Townsdaye and	Deller, Narisa
ater Well Contrac	TD 17	, 7 . 7	Inis Wa	rei Aveil Heco	ru was complet	eu on (mo/day/yr		2 1 2 2 3 Y	
	, JR En	vironmen	tal Drill	lng			<i>ን</i> ሰለ ለላኔ	נומותו	
der the business	name of JB EII e typewriter or ball point pe	vironmen	tal Drill			gnature)	neadou	RUL	