## GSI Job No. 047285

	WATER WELL RECOR	D Form WWC-5	KSA 82a-1	212 ID No			
1 LOCATION OF WATER WELL:	Fraction		tion Number		ber	Range	e Number
County: Reno	SW ½ SW ½		16	т 23	S	R	<b>05</b> w
Distance and direction from nearest tow 3300 E Avenue G	n or city street address of well if lo	cated within city?					
2 WATER WELL OWNER:	Kaneb Pipeline Compa						
RR#, St. Address, Box # :	7340 W 21 <sup>st</sup> St. N. Ste 2	200		Board of Agricult	ure, Divis	ion of Wat	er Resources
City, State, ZIP Code :	Wichita, Kansas			Application Num	ber:		
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WE	20	+ ELE)				
N	Depth(s) Groundwater Encounter						
	WELL'S STATIC WATER LEVEL						
! ! NW NF	Pump test data: We						
NE	Est. Yield gpm: We						
₩ W E	Bore Hole Diameter 8.5	in to 2	0	ft and	in in	to	
	WELL WATER TO BE USED AS:	5 Public water s	upply	8 Air conditionir	ng 11	Injection	well
SW SE	WELL WATER TO BE USED AS: 1 Domestic 3 Feed lot	6 Oil field water	supply	9 Dewatering	12	Other (S	pecify below)
•   ×	2 Irrigation 4 Industrial	7 Lawn and gar	den (domestic	<li>c) 10 Monitoring w</li>	/ell	Air Spa	rge Well
S S	Was a chemical/bacteriological sa	ample submitted to l	Department?	Yes No X	If yes,	mo/day/yr	sample was
~	submitted		Wa	ter Well Disinfected?	Yes	11	No X
5 TYPE OF BLANK CASING USED:		on 8 Concr	ete tile	CASING JOINT	S: Glued		Clamped
1 Steel 3 RMP (	SR) 6 Asbestos-0	Cement 9 Other	(specify belo	w)	Welde	d	
2 PVC 4 ABS	7 Fiberglass				Thread	led	Flush
Blank casing diameter 2	in. to <b>18</b> ft., Dia	in, t	to	ft., Dia		in. to	ft.
Casing height above land surface	12 in., weight	0.703	lbs./ft.	Wall thickness or ga	uge No.	S	ch 40
TYPE OF SCREEN OR PERFORATION		7	PVC	10 Asbest	os-cemer	nt	
1 Steel 3 Stainle	ess steel 5 Fiberglass						
2 Brass 4 Galvan	nized steel 6 Concrete ti	le 9	ABS	12 None u	used (ope	n hole)	
SCREEN OR PERFORATION OPENIN		Gauzed wrapped		8 Saw cut		11 None	(open hole)
1 Continuous slot 3	Mill slot 6	Wire wrapped		9 Drilled holes			
2 Louvered shutter 4		Torch cut		10 Other (specify	)		
SCREEN-PERFORATED INTERVALS:	From <b>18</b> ft. to	20	ft. F	rom	ft. to		ft.
	Fromft. to		ft. F	rom	ft. to		ft.
GRAVEL PACK INTERVALS:	From <b>17</b> ft. to	20		rom	ft. to		ft.
······	From ft. to		ft. F	rom	ft. to	)	ft.
6 GROUT MATERIAL: 1 Neat c	cement 2 Cement grout	3 Ben	tonite	4 Other Bentor	nite Gro	out	
Grout Intervals From <b>2</b>	ft. to 16 ft. From	<b>16</b> ft.	to <b>17</b>	ft. From		ft. to	ft.
What is the nearest source of possible c	contamination:			tock pens	14 Aba	ndoned w	ater well
	4 Lateral lines 7 P			-		well/ Gas v	
2 Sewer lines		ewage lagoon		zer storage	16 Oth	er (specify	below)
3 Watertight sewer lines	6 Seepage pit 9 F	eedyard		ticide storage			
Direction from well? FROM TO CODE	LITHOLOGIC LOG	FROM	How many		CINC IN	TERVALS	
	t/Clayey Silt					1 LI WILLO	
6 20 Sa							
					REC	EIVE	Ð
			·		NOV-2	<b>9</b> 200	4
						200	
				BUI	REAU	OF WA	TER
			_				
7 CONTRACTOR'S OR LANDOWNER				•			1
completed on (mo/day/yr)				rve to the best of my			
Water Well Contractor's License No.				ecord was complete		day/yr)	11-19-04
	Geotechnical Services, I		gnature)	Uluon	M	VR.	5
INSTRUCTIONS: Please fill in blanks	s and circle the correct answers. Sen is 66612-1367. Telephone: 913-296-						ater, 1000 S W

Form provided by Forms-On-A-Disk, Inc. · Dallas, Texas · (214) 340-9429

AS 65