4 1 004	ONLOGIAZATE	DWELL			VELL RECO	JKD FO	orm WWC-5		A 82a-1:		U. and b. c		Nivers	
	ON OF WATE		Fraction		SW ½	SE	1		umber				Number	
County:		eno m nearest tow	SW stre					16		T 23	<u> </u>	R	05	W
3	300 E Ave	nue G												
	WELL OWNE		Kaneb F											
ľ	dress, Box#		7340 W			e 200				Board of Agr	iculture, Div	ision of Wate	er Resou	ırces
City, State,	ZIP Code	:	Wichita	<u>, Kans</u>	as					Application N	lumber:			
3 AN "X" IN	A SECTION B	CATON WITH OX:	4 DEPTH	OF COM	IPLETED V	WELL	20	)ft	. ELEV	ATION:				
_	N		Depth(s) Gr	oundwat	er Encount	tered 1		<b>-</b>	ft.	2	ft.	3	- <b></b>	ft. OF
1										urface measured				្ត
	N'W	- NE		Pump tes	st data: V	Vell water	r was		ft	i. after	hours	oumping		gpm C
<u>o</u>			Est. Yield		gpm: V	Vell water	r was	<b></b>	ft	t. after	hours	oumping		
- W €		┿┪╘	Bore Hole D	Diameter	8.5	in. to		0		ft. and 8 Air conditi		n. to		ft.   O
	sw	ļ_												
	· ·	- SE	2 Irrig	ation 4	1 Industria	171	awn and car	supply	/ omastir	<ol> <li>9 Dewaterir</li> <li>10 Monitorii</li> </ol>	ig ng well	Air Sna	rae We	ow)
♦	X									Yes No				
	S		submitted	nical/bac	teriological	sample	Submitted to	Depart		ter Well Disinfec				
5 TYPE OF	F BLANK CAS	SING USED:		5	Wrought	Iron	8 Conc	rete tile		CASING JO				
1 Ste		3 RMP(	(SR)		_		t 9 Other				Weld			
2 PV		4 ABS			Fibergla								Flush	
Blank casing	g diameter	2	in. to	18	ft., Dia		in.	to		ft., Dia Wall thickness o		in. to		ft.
Casing heig	ht above land	surface	12	in.,	weight		0.703		lbs./ft.	Wall thickness of	or gauge No	S	ch 40	
		ERFORATIO	N MATERIAL	_:			7	PVC		10 As	bestos-cem	ent		
1 Ste		3 Stainle					8	RMP	(SR)	11 Oti	ner (specify)			-
2 Bra		4 Galvar ION OPENIN		6	Concrete		9 ed wrapped	ABS		12 No 8 Saw cut		en hole) 11 None (	opon ho	10)
	ntinuous slot		Mill slot				wrapped			9 Drilled hole		ii None (	openno	,6,
		4		d		7 Torch				10 Other (spe				ĺ
		INTERVALS:							ft. F	rom	ft	to		ft
										rom				
GRA	AVEL PACK I	NTERVALS:	From	17	ft.	to	20		ft. F	rom	ft.	to		ft.
			From						ft. F	rom	ft.	to		ft.
6 GROUT	MATERIAL:	1 Neat o	cement	2 Ce						4 Other Ben				
Grout Interv	als From	2	ft. to	16	ft. From	1	6 ft.	to	17	ft. From		ft. to		ft.
		e of possible of								tock pens		andoned wa		
1 Sep	otic tank		4 Lateral I			Pit privy		11	Fuel s	storage				1
	wer lines		5 Cess po			Sewage	-			zer storage	16 O	her (specify	below)	
İ	tertight sewer	lines	6 Seepage	e pit	9	Feedyar	ď			ticide storage		• • • • • • • • • • • • • • • • • • • •		
Direction fro FROM	TO	CODE	117	THOLOG	ICLOG		FROM		v many		LUGGING	NTERVALS		
0	6		t/Clayey				1 110				200011101	TTETTTE		
6	20	Sa	nd											
												-050		
								+-				CEIV	ED-	
											NO.	1000	004	
							+				INU	<b>√ 2 9</b> 2	004	
								+			BURE	AU OF W	ΙΔΤΕΓ	5
											JOI (L)	10 OI V		
								-						
								+-						
7 CONTRA	ACTOR'S OR	LANDOWNE	R'S CERTIFI	CATION	: This wate	er well wa	s (1) constru	icted.	(2) reco	onstructed, or (3)	plugged un	der my jurisd	iction an	d was
ļ——i	on (mo/day/yr)			10-7-0						ue to the best o				1
l .	Contractor's L				531					ord was comp			11-19	
1	usiness name		Geotechr	nical S	ervices	, inc.		ignatur		Llie	n M	1.1/2		
							copies to Kar	sas De	patmer	nt of Health and E			er, 1000	s w