WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.	
	Number
)5 W
Distance and direction from nearest town or city street address of well if located within city? 3300 E Avenue G	
2 WATER WELL OWNER: Kaneb Pipeline Company	
RR#, St. Address, Box # : 7340 W 21 st St. N. Ste 200 Board of Agriculture, Division of Water	Pacourcae
City, State, ZIP Code : Wichita, Kansas Application Number:	1103001003
LOCATE WELL'S LOCATON WITH	
3 AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION:	
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3	
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr	
NW	
Est. Yield gpm: Well water was ft. after hours pumping	gpm.
Bore Hole Diameter 8.5 in. to 20 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection w 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Spe	ft.
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Spe	cify helow)
1 2 Irrigation 4 Industrial 7 Lournand garden (demontic) 40 Manitaring well 1 Air Sport	ge Well
Was a shamisal/hasteriological comple submitted to Department? Yes	
submitted S Was a Chemical bacteriological sample submitted to Department? Yes No. A lifyes, mordayryr sa submitted Water Well Disinfected? Yes No.	
5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Cla	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	ampeu
	luch
	iusii
Blank casing diameter 2 in. to 18 ft., Dia in. to ft., Dia in. to	ft.
Casing height above land surface 12 in., weight 0.703 lbs./ft. Wall thickness or gauge No. Sc	n 40
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (o	non holo)
	pen noie)
SCREEN-PERFORATED INTERVALS: From 18 ft. to 20 ft. From ft. to	
Fromft. toft. Fromft. toft. Fromft. toft. ft. fromft. ft. from	П.
	II.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Grout	
Grout Intervals From 2 ft. to 16 ft. From 16 ft. to 17 ft. From ft. to	
What is the nearest source of possible contamination: 10 Livestock pens 11 Abandoned wat 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas we	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas we 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify b	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	elow)
Direction from well? How many feet?	
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 6 Silt/Clayey Silt	
6 20 Sand	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
NOV 2 9 2004	
NOV 2 9 2004	
	=R
NOV 2 9 2004 BUREAU OF WATE	ER
	ER
	R
	≣R
BUREAU OF WATE	
BUREAU OF WATE CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdice.	ction and was
BUREAU OF WATE 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdic completed on (mo/day/yr) 10-7-04 and this record is true to the best of my knowledge and believed.	ction and was
BUREAU OF WATE 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdic completed on (mo/day/yr) 10-7-04 and this record is true to the best of my knowledge and believed.	ction and was