				ER WELL RECORD			-1212 ID No	
LOCATI	ON OF WATE		f			Section Number		Range Number
County:			SW ¼				T 23 S	R 05 W
Distance and direction from nearest town or city street address of well if located within city? 3300 E Avenue G								
2 WATER	WELL OWNE	R:	Kaneb Pipe	eline Compar	ny			
RR#, St. Ad	ldress, Box#	:	7340 W 21 ^s	^t St. N. Ste 2	200		Board of Agriculture, I	Division of Water Resources
City, State,	ZIP Code	: .	Wichita, Ka	ınsas			Application Number:	İ
3 LOCATE AN "X" II	WELL'S LOC N SECTION B	CATON WIT	DEPTH OF C	COMPLETED WEI	LL	15 ft. EL		
	N		Depth(s) Ground	lwater Encountere				. 3 ft.
A								ay/yr
	NW	- NE						rs pumping gpm
	· · · · ·		Est. Yield	gom: Well	l water was		ft after hou	rs pumpinggpm
₩ W L			E Bore Hole Diame	eter 8.5 in	n to	15	ft and	in. to ft.
7			WELL WATER T	O BE USED AS:	5 Public wat	er supply	8 Air conditioning	11 Injection well
	sw -	SE	1 Domestic	3 Feed lot	6 Oil field wa	ter supply		12 Other (Specify below)
	X		2 Irrigation	4 Industrial	7 Lawn and	garden (domes	tic) 10 Monitoring well	Air Sparge Well
	S		Was a chemical/	bacteriological sar	mple submitted	to Department	? Yes No X If y	es, mo/day/yr sample was
			submitted				/ater Well Disinfected? Yes	
5 TYPE O	F BLANK CAS	SING USED):	5 Wrought Iro	n 8 Co			
5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded								
2 PVC 4 ABS 7 Fiberglass Threaded Flush								
		— 2				in to		
Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 0.703 lbs./ft. Wall thickness or gauge No. Sch 40								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1				5 Eiberglass				į
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 13 ft. to 15 ft. From ft. to ft.								
From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 12 ft. to 15 ft. From ft. to ft.								
0.0			From					ft. to ft.
6 CPOUT	MATERIAL	1 Nos			2	Pontonito	4 Other Bentonite	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Grout Grout Intervals From 2 ft. to 11 ft. From 11 ft. to 12 ft. From ft. fr. ft. to ft.								
				ft. From	Т			t t
I			e contamination:	7 00	t mais a c			Abandoned water well
			4 Lateral lines				l storage 15	1
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction fro	-		o occpage pit	3 10	cayara	How mar		
FROM	TO	CODE	LITHOL	OGIC LOG	FRO			SINTERVALS
0	6	S	Silt/Clayey Silt					
6	15	S	Sand					
								ECEIVED
							 	
							N/	OV 2 9 2004
							l N	7 4 4 7 7 1 1 1 1 1
							DUD	AU OF WATER
							BURI	AU OF WATER
7 60:	07075 55		EDIA 6					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was								
completed on (mo/day/yr) 10-7-04 and this record is tratego the best of my knowledge and belief. Kansas								
Water Well	Contractor's L	icense No.		531	Th	is Water Well J	Record was completed on	mo/day/yr) /11-19-04
	usiness name		Geotechnica		IC. by	(signature)	Muxon of	H Arm
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								
3401301		. spend, ridi		-p	J. J	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		