

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SW 1/4 SW 1/4 SE 1/4	2	T 23 S	R 5 E
Distance and direction from nearest town or city street address of well if located within city?					
2 mi E of Hutchinson - 5408 E 17th					
2 WATER WELL OWNER: Cleo Dutton					
RR#, St. Address, Box # : 5408 E 17th			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Htch, KS 67501			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 56 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 11-18-04			
		Pump test data: Well water was 51 ft. after 2 hours pumping 25 gpm			
		Est. Yield 25 gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 31 ft. Dia 5 in. to 56 ft. Dia in. to					
Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 16.0					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-Cement		11 Other (Specify)	
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes		10 Other (specify)	
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 31 ft. to 51 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 57 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 55			
Direction from well? W					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 8 Sandy Br Clay					
8 25 Br + Gr Clay					
25 42 F Sand					
42 46 Br + Gr Clay					
46 51 F Sand					
51 57 Br Clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-18-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 447 This Water Well Record was completed on (mo/day/yr) 12-8-04 under the business name of Miller Drilling by (signature) E. Miller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					