WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.
LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
ounty: Reno NE ½ NW ½ NW ½ 6 T 23 S R 5 E/
istance and direction from nearest town or city street address of well if located within city?
warman and Dale Smyree Dele's Northgate
WATER WELL OWNER: Dale Smyres Dale's Northgate
R#, St. Address, Box # : 629 E. 30th Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Hutchinson, KS 67502 SV-4 Application Number:
AN "X" IN SECTION BOX:
N Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
W ELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 A Demostic 2 Food lat 6 Oil food water surply 0 Demotoring 12 Other (Constituteday)
Soil Vent
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Soil Vent
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was
submitted Water Well Disinfected? Yes No X
5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped
Steel         3 RMP (SR)         6 Asbestos-Cement         9 Other (specify below)         Weided
2 PVC 4 ABS 7 Fiberglass Threaded X
Casing height above land surface in., weight Ibs./ft. Wall thickness or gauge No Ibs./ft. Wall thickness or gauge No PVC 10 Asbestos-cement
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel     3 Stainless steel     5 Fiberglass     8 RMP (SR)     11 Other (specify)       2     2     2     2     2     2
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  12 None used (open noie)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped (a) Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 9 ft. to 19 ft. From ft. to ft.
Fromft. toft. Fromft. toft.
GRAVEL PACK INTERVALS: From 8.5 ft. to 14.5 ft. From ft. to ft.
From 14.5 ft to 19 ft From ft to ft
6 GROUT MATERIAL: 1 Neat cement Ocement grout 3Bentonite 4 Other
Grout Intervals From 0 ft. to 3 ft. From 3 ft. to 8.5 ft. From ft. to ft.
What is the nearest source of possible contamination:       10       Livestock pens       14       Abandoned water well
1 Septic tank     4 Lateral lines     7 Pit privy     11 Fuel storage     13 Oil well/ Gas well       2 Septic tank     4 Lateral lines     7 Pit privy     11 Fuel storage     13 Oil well/ Lateral lines
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 19 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site
Direction from well?
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 .5 Cement
.5 2 Fill
2 9 Brown very clayey to sandy Cly
9 12 Fine to very fine grained Sand
12 19 Grades to mixed Sands
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) 2-15-05 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 04-07-05
under the business name of Woofter Pump & Well Inc. by (signature)
Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

1