

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		NW 1/4 NW 1/4 SE 1/4	6	T 23 S	R 5 E
Distance and direction from nearest town or city street address of well if located within city? 1002 E 21st Hutchinson, KS 67502					
2 WATER WELL OWNER: Jesse Castillo RR#, St. Address, Box # : City, State, ZIP Code : 1002 E 21st Hutchinson, KS 67502					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL			
		ft. ELEVATION: 512.04			
		Depth(s) Groundwater Encountered: 12.5 ft. 2 14 ft. 2 12.5 ft.			
		WELL'S STATIC WATER LEVEL 12.5 ft. below land surface measured on mo/day/yr 5-18-05			
		Pump test data: Well water was 1 1/2 ft. after 1 1/2 hours pumping 25 gpm			
		Est. Yield 25 gpm: Well water was 1 1/2 ft. after 1 1/2 hours pumping 25 gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to 22 ft. Dia 22.9 in. to 160 in. to					
Casing height above land surface 12 in., weight 22.9 lbs./ft. Wall thickness or gauge No. 160					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement					
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft., From 12.5 ft. to 32 ft., From					
GRAVEL PACK INTERVALS: From 12.5 ft. to 32 ft., From					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 12.5 ft., From					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? S How many feet? 15'					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 10 Dirt					
10 12.5 Sand					
12.5 32 Gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-18-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 15885 This Water Well Record was completed on (mo/day/yr) 5-18-05 under the business name of Wilson Water Systems by (signature) Eric Wilson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					