

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SE 1/4 SE 1/4		Section Number 6		Township Number T 23 S		Range Number R 5 E/W	
County: Reno									
Distance and direction from nearest town or city street address of well if located within city? 27 Lawndale Park in Hutch									
2 WATER WELL OWNER: Don Miller									
RR#, St. Address, Box #: 27 Lawndale Park									
City, State, ZIP Code: Hutch, KS 67502									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 4.0 ft. ELEVATION:									
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 6-24-05							
		Pump test data: Well water was 17 ft. after 14 hours pumping 85 gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded									
Blank casing diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 160									
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement									
1 Steel 3 Stainless Steel 8 RMP (SR) 11 Other (Specify)									
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continuous slot 3 Mill slot 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 22 ft. to 43 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 2 ft. to 22 ft., From ft. to ft.									
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well									
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? NW How many feet? 40									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 9 Br Clay									
9 43 Sand + Gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-24-05 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's Licence No 447 This Water Well Record was completed on (mo/day/yr) 7-17-05									
under the business name of Miller Drilling by (signature) E Miller									