

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Reno		SW 1/4 NE 1/4 SW 1/4		9		T 23 S		R 5 EW			
Distance and direction from nearest town or city street address of well if located within city?						816 North Halstead Hutchinson, KS 67501					
1445' North & 1810' East of Fourth & Halstead Intersection; ADM Terminal J											
2 WATER WELL OWNER: City of Hutchinson											
RR#, St. Address, Box # : Post Office Box 1567											
City, State, ZIP Code : Hutchinson, KS 67504											
Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.									
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter .72 in. to .17 ft., and in. to ft.									
WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Soil vapor extraction											
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> X; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No <input checked="" type="checkbox"/> X											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <input checked="" type="checkbox"/> X											
Blank casing diameter 4 in. to 10 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 6 bls in., weight lbs./ft. Wall thickness or gauge No. Schedule 40											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 0.010 Slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 10 ft. to 15 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 8 ft. to 17 ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Neat Cement with 3% bentonite											
Grout Intervals: From 5 ft. to 6 ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? How many feet?											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		2		Brown clayey silt with gravel & pebbles		6		8		Pure Gold bentonite chips 3/8"	
2		4		Dark brown clayey silt		5		6		Neat cement with 3% bentonite	
4		10		Brown sandy silty clay		3		5		Pure Gold Bentonite Chips 3/8"	
10		15		Brown and gray silty clay		2		3		Compacted soil	
						0		2		Flush mount well protector set in a concrete pad 2 x 2 x 2	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-22-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 655 This Water Well Record was completed on (mo/day/yr) 10/7/05 under the business name of Philip Environmental Services Corporation by (signature) <i>John E. J...</i>											