

1 LOCATION OF WATER WELL: County: Reno Fraction: NE 1/4 NE 1/4 SE 1/4 Section Number: 21 Township Number: T 23 S Range Number: R 5 E(W)

Distance and direction from nearest town or city street address of well if located within city? 1/2 mi. N. & 1/2 mi. W. of Yoder Rd. & Blanchard

2 WATER WELL OWNER: Mosaic Company RR#, St. Address, Box #: 1800 Cary Blvd. City, State, ZIP Code: Hutchinson, KS. Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section grid with NW, NE, SW, SE quadrants and X in SE quadrant]

4 DEPTH OF COMPLETED WELL: 8 ft. ELEVATION:

Depth(s) Groundwater Encountered 1 7 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

- 1 Domestic
- 2 Irrigation
- 3 Feedlot
- 4 Industrial
- 5 Public water supply
- 6 Oil field water supply
- 7 Domestic (lawn & garden)
- 8 Air conditioning
- 9 Dewatering
- 10 Monitoring well
- 11 Injection well
- 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

- 1 Steel
- 2 PVC
- 3 RMP (SR)
- 4 ABS
- 5 Wrought iron
- 6 Asbestos-Cement
- 7 Fiberglass
- 8 Concrete tile
- 9 Other (specify below)

CASING JOINTS: Glued Clamped Welded Threaded

Blank casing diameter in. to ft., Dia in. to ft.

Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel
- 2 Brass
- 3 Stainless Steel
- 4 Galvanized Steel
- 5 Fiberglass
- 6 Concrete tile
- 7 PVC
- 8 RMP (SR)
- 9 ABS
- 10 Asbestos-Cement
- 11 Other (Specify)
- 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot
- 2 Louvered shutter
- 3 Mill slot
- 4 Key punched
- 5 Gauzed wrapped
- 6 Wire wrapped
- 7 Torch cut
- 8 Saw cut
- 9 Drilled holes
- 10 Other (specify) ft.
- 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 3 ft. to 8 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 2 ft. to 8 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other.....

Grout Intervals: From 1 ft. to 2 ft., From 3 ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

- 1 Septic tank
- 2 Sewer lines
- 3 Watertight sewer lines
- 4 Lateral lines
- 5 Cess pool
- 6 Seepage pit
- 7 Pit privy
- 8 Sewage lagoon
- 9 Feedyard
- 10 Livestock pens
- 11 Fuel storage
- 12 Fertilizer storage
- 13 Insecticide storage
- 14 Abandoned water well
- 15 Oil well/Gas well
- 16 Other (specify below) Silt plant

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1'	Topsoil			
1	3'	Silt			
3	8'	Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-25-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 604. This Water Well Record was completed on (mo/day/yr) 11-30-05 under the business name of Environmental Priority Service by (signature) PA...